

Process Integration, Modelling and Optimisation for Energy Saving and Pollution Reduction

Ferenc Friedler

Faculty of Information Technology, University of Pannonia
Egyetem utca 10, H -8200 Veszprém, Hungary
friedler@dcs.uni-pannon.hu

Energy saving, global warming and greenhouse gas emissions have become major technological, societal, and political issues. Being closely related to energy supply, they are of strategic importance. Various conferences are being organised for providing international avenues for closer cooperation among researchers.

The series of conferences “Process Integration, Modelling and Optimisation for Energy Saving and Pollution Reduction” (PRES) play a pioneering role in contributing to the solution of the related problems through presenting new methodologies and initiating cooperation among participants that often result in international projects. The PRES conferences have been dedicated both to the theoretical and to the practical components of the problems of energy saving and pollution reduction. The PRES series, established twelve years ago, was originally dedicated to energy integration and improving thermal efficiency. Following the new challenges and priorities the scope of the conferences has been extended to include all energy and pollution prevention related issues.

This contribution focuses on the period covered by PRES, reviewing at least some major presentations contributing to the development of process integration and optimisation tools for energy saving and pollution reduction. The development of the mathematical models has been covered as well, since it is closely related to the area.

1. Process Integration

Process integration is a family of methodologies for combining several processes to reduce consumption of resources or harmful emissions to the environment. It started as mainly heat integration stimulated by the energy crisis in the 1970's.

1.1. Early Stages of Process Integration

It is remarkable that process integration has not lost the interest of researchers for 35 years and even has been flourishing recently. One of the first related works was that by Hohmann (1971) in his PhD thesis at the University of Southern California. He has not pursued the research any further and in that “ancient pre-internet age” its enormous potential has not been recognised by the research community at that time.

It was Bodo Linnhoff and his PhD supervisor the late John Flower at University of Leeds who continued this work. They used Hohmann's work and in 1977 developed the basis of pinch technology, which is now considered as the foundation of heat

integration. As usual in case of a pioneering innovation, it was difficult to publish. The first publications appeared in 1978 (Linnhoff and Flower, 1978) due to their strong commitment. This has become the most cited paper in the history of chemical engineering. A similar work has been done in Japan more or less in parallel (Umeda *et al.*, 1978, 1979). It was again Linnhoff who pushed the new concept through the academia and the industry. An important step was his arrival, via an industrial appointment at ICL Ltd in Runcorn, Cheshire, to that time UMIST where he set up the Centre for Process Integration and the Process Integration Research Consortium.

1.2. Pinch Technology for Heat Integration

The publication of the first “red” book by Linnhoff *et al.* (1982) played a key role in the dissemination of heat integration. The book received a new Foreword (1994) reflecting the up to date developments. It has been massively cited in the literature and is considered as the first overview of the area. This User Guide through pinch analysis provided insight into the most common process network design problems including heat exchanger network synthesis, heat recovery targeting, and selecting multiple utilities.

Heat recovery targeting is based on the Composite Curves (CC) (Linnhoff *et al.* 1979). This is a visual tool, providing important energy-related properties of an industrial process in a single view. The overlap between the curves represents the heat recovery target, while the needs for external heating and cooling are represented by the non-overlapping segments of the cold and hot composite curves, respectively. Most importantly, these thermodynamically derived heat recovery targets been exceeded by any real system. CCs play an important role in process design. For direct Heat Exchanger Network (HEN) synthesis algorithms, they provide strict targets for Maximum Energy Recovery (MER). For process synthesis based on Mathematical Programming, they provide relevant lower bounds on utility requirements and capital cost, narrowing the search space of the optimisation. The recognition of the thermodynamic limitations and relationships in the underlying heat recovery problem has led to the development of the Pinch Design Method (Linnhoff and Hindmarsh, 1983). This method is capable of producing maximum heat recovery networks.

A further development for Heat Integration targeting has been the Grand Composite Curve (GCC) (Townsend and Linnhoff, 1983), together with the associated Heat Cascade and the Problem Table Algorithm (Linnhoff and Flower, 1978). The GCC shows a clearer view of the areas of internal heat recovery as well as the demands for external heating and cooling – all in the context of the corresponding temperature levels. The appropriate combination of utilities can be targeted aiming at minimal emissions and/or utility costs.

1.3. Mass and Water Pinch

Inspired by the success of Heat Integration, researchers have spread the Pinch idea to other areas – in particular to mass exchange (El-Halwagi and Manousiouthakis, 1989). Wang and Smith (1994) developed a method for industrial Water Networks as a special case of Mass Exchange Networks. The main objective was to simultaneously minimise the consumption of fresh water and the disposal of wastewater by maximising the internal water re-use. The wastewater generation can be further reduced by applying additional operations for water regeneration, allowing further re-use or recycling. For cases of single-contaminant problems, translating the Pinch Analysis to water

minimisation is straightforward, constructing the composite curve of water use as a plot of the contaminant concentration versus contaminant load. Extending the Water Pinch Analysis to multiple-contaminant problems, however, is complicated and difficult to use. The major issue is which one contaminant to plot on the composite curves. Many approaches are available. One useful option is to employ Mathematical Programming; where Water Pinch serves as a preliminary scoping and visualisation tool.

1.4. Other Pinch based Methodologies

The Pinch Principle has also been applied to other types of processes and areas, the most prominent being Total Site Integration, refinery hydrogen management, Carbon Footprint estimation/minimisation, and wastewater treatment.

1.4.1. Hydrogen Pinch

Previously hydrogen availability was not a problem for refineries. Several new trends have caused an increased demand for hydrogen. A methodology has been developed for assessing the available hydrogen resources on a site, using the so-called Hydrogen Pinch Analysis (Alves, 1999). It constructs Hydrogen Composite Curves accounting for the demands and sources of hydrogen on a site in terms of stream purity vs. flowrate. That is used to construct a hydrogen surplus diagram similar to the GCC in Heat Integration. These instruments allow engineers to find the system Hydrogen pinch and set targets for hydrogen recovery, production and import by a refinery. This methodology has been improved by Hallale and Liu (2001) accounting for pressure as a factor and, therefore, making the best use of the existing compressors in the refinery. This improved method can also account for important costs and tradeoffs including hydrogen production, compressors, fuel, and piping costs.

1.4.2. Oxygen Pinch

The strive to design more cost efficient waste treatment systems inspired yet another extension of the pinch principle – the Oxygen Pinch Analysis (Zhelev and Ntlhakana, 1999). The idea was to target prior to design the ideal minimum oxygen demands for micro-organisms aeration. Flowsheet and design changes were suggested based on the target. Agitation and other forms of aeration require energy, so finally, the analysis based on oxygen pinch principles leads again to their original application associated with energy conservation. The method also provides other indicators – quantitative targets for oxygen solubility, residence time, and oxidation energy load. In a follow-up development, a combined Water-and-Oxygen Pinch Analysis has been proposed (Zhelev and Bhaw, 2000). By combining the two criteria, up to 30 % cost savings for the wastewater treatment could be achieved.

1.4.3. Total Site

To develop a good understanding of industrial energy systems, a graphical method has been developed based on the concept of the Total Site (Dhole and Linnhoff, 1993). They have introduced the concept of the site's heat source and heat sink profiles. By integrating a number of processes via the steam system, additional inter-process heat recovery can be achieved by using the total site profiles as guides. The method allows a target to be set for the total site heat recovery. Data for process heat recovery are first converted to GCCs. The pockets of the GCCs representing the scope for process to process heat recovery are removed and the modified GCCs are combined to form a site

heat source profile and a site heat sink profile. The sink and source profiles are superimposed on the steam header saturation temperatures and composite curves of steam generation and usage are constructed, accounting for feasible heat transfer from the heat source profile to the steam generation composite and from the steam usage composite to the heat sink profile. The work by Dhole and Linnhoff (1993) and Raissi (1994) was further developed by Klemeš *et al.* (1997). On the basis of the Steam Composite Curves, thermodynamic targets for heat and power cogeneration can be set. The cogeneration targeting model has been refined by Mavromatis and Kokossis (1998) and further improved by Varbanov *et al.* (2004).

1.5. Contributions of PRES Conferences

PRES Conferences contributed considerably to the development of Process Integration methodologies and dissemination of successful case studies.

1.5.1. PRES' 98

Bodo Linnhoff presented one of his last plenary lectures (Linnhoff and Akinradewo, 1998) on the automated interface between simulation and integration. This has been a substantial step towards data extraction for process integration software tools. The plenary has been rather comprehensive and suggested the way forward for this important task. This problem received some interest during the following years and several software packages have been offering support for this task. Despite this, more work should be done to satisfy the needs for industrial applications.

Recent trends in Process Integration, software and applications were presented by Gundersen (1998). He proclaimed an important development of Hybrid Process Integration methods created by merging previously competing schools – Pinch Technology and Mathematical programming.

Bochenek *et al.* (1998) compared retrofitting of flexible HENs by optimisation versus simulation approach. This has been very important work in the field which still deserves more research.

Zhu *et al.* (1998, 2000) proposed heat transfer enhancement for heat exchanger network retrofit design, from which Heat Integration can substantially benefit. This methodology still deserves wider implementation especially for retrofit studies.

Hassan *et al.* (1998, 1999) presented a successful process integration analysis and retrofit suggestions for a FCC plant. It was one of the first comprehensive retrofit case studies.

Kalitventzeff *et al.* (1998) covered usefulness of Process Integration in the application to the isothermal gas turbine. Plešu *et al.* (1998) demonstrated the wide applicability of Process Integration in the Romanian oil refining and petrochemical industry.

Klemeš *et al.* (1998), made a series of applications of Pinch-technology in the food industry. This has been further developed in (Klemeš *et al.*, 1998). They had shown that Pinch technology can provide benefits far beyond oil-refining and petrochemicals.

Mařík *et al.* (1998) and Burianec *et al.* (1999) presented a design tool for flexible and energy efficient HENs. This approach has been based on an expert system and optimisation.

1.5.2. PRES'99

This forum was held in Budapest – Hungary. It has been a major step in the development of the conference – both in terms of number of the participants and in the scope of covered areas. Plenary lecture Smith (1999) made an overview of Process Integration.

Zhu and Vaideeswaran (1999) reviewed an extension of the Total Site methodology – the Top Level Analysis. This approach has considerable potential, yet to be realised.

Fraser and Hallale (1999) attempted effluent reduction through pinch technology and demonstrated it on gold solvent extraction plant. Interesting extension was also an impact diagram showing effluent reduction versus capital investment target.

Hashemi-Ahmady *et al.* (1999) came up with a sequential Framework for Optimal Synthesis of Industrial HENs by combining Pinch Analysis and simultaneous MINLP methods. The idea has been further developed at following PRES conferences.

Zhelev and Bhaw (1999) introduced an Oxygen Pinch Analysis and combined it with water Pinch Analysis for wastewater management.

Klemeš *et al.* (1999) summarised a comprehensive experience of retrofitting Polish Sugar Factories using Process Integration. They presented the implementation of Heat Integration up to Total Site level considering retrofit features in combination with process modifications, based on close collaboration with the staff from the factories.

Aaltola (1999) suggested through case studies the integration of a paper mill with two sites district heating including seasonal variations. However, at that stage several important issues have been just drafted and opened for the future research. Another case study dealt with heat and exergy analysis of biomass fuelled integrated gasification humid air turbine (BIO-IGHAT) plant (Assadi and Johansson, 1999). This is a new class of problems simultaneously applying heat integration and exergy analysis.

Dogru *et al.* (1999) performed a case study – using a software tool from Linnhoff March (SuperTarget, 1997) for an ammonia plant. However, the analysis covered just the first step and did not continue into advanced heat integration steps.

Galli and Cerda (1999) adopted an approach based on MINLP for the synthesis of HENs featuring a minimum number of bounded-size shells. Their approach would benefit from its combination with process integration.

Rodera and Bagajewicz (1999) suggested a heat integration approach across plants of multipurpose heat exchangers. They extended the Minimum Matching Approach of Papoulias and Grossmann (1983). Their targeting procedure has been further developed.

Gottschalk *et al.* (1999) applied a Heat Integration Expert System for energy integration of industrial chemical processes. Its interesting feature was the combination with Pinch technology, which was demonstrated on an industrial case study for the synthesis of Methyl-tert-butyl-ether. This approach has still a good potential to be explored further.

A well developed industrial case study was presented by Markowski (1999) – a retrofit of crude distillation unit. He covered important features of fouling and brought this case study close to the industrial conditions.

Seikova *et al.* (1999) presented a retrofit debottlenecking of a heat integrated crude oil distillation system Building upon previous works of the UMIST team – (Asante and Zhu, 1996) as well as from the approach presented by Varbanov and Klemeš (1999, 2000).

Tovazhyansky *et al.* (1999) used the heat integration methodology spread by the collaboration with UMIST under the UK Know-How fund district heating, chemical industry, ammonia plants, and food and drink industry across Ukraine.

1.5.3. PRES 2000

Kalitventzeff *et al.* (2000, 2001) emphasised that better solutions can be generated for process sustainability through process energy integration. They shared their experience in the implementation of process energy integration techniques and their contribution to the process sustainability in an ammonia plant including combined production of heat and mechanical power for an existing process.

Pinch technology and its recent extensions offer an effective and practical method for designing the HEN for new and retrofit projects. Al-Riyami *et al.* (2000, 2001) demonstrated a heat integration retrofit analysis of a HEN of a fluid catalytic cracking (FCC) plant. The study found significant scope for improvement in the heat recovery. The new network was designed using the network pinch method.

Grabowski *et al.* (2000, 2001) presented a case study of energy minimisation in sugar production by applying process integration. The minimum energy consumption of the process was determined by simultaneous energy targeting and optimisation of evaporation. Energy systems employing various CHP technologies and various evaporator stations optionally combined with vapour compressors are studied. A range of feasible solutions is defined in terms of minimum energy consumption and combined heat transfer area of the evaporator station and the heat exchanger network.

1.5.4. PRES'01

Sadhukhan and Zhu (2001) examined the integration of gas technologies in the context of overall refinery in order to use gasification for stretching the economic margins to the full extent. A stage-wise optimisation strategy was developed in order to capture interactions among refinery processes, the gasification system and hydrogen and utility networks.

Integration of waste to energy is a good option for thermal processing of waste. Bébar *et al.* (2001, 2002) demonstrated the method of efficiently utilising the heat value of the incineration products and thus partially compensate the costs of waste thermal treatment.

Chuang *et al.* (2001, 2002) addressed another important aspect in process integration. They presented the Total-Site Maintenance Scheduling for better energy utilisation. To minimise the impacts on production and utility systems during routine maintenance the scheduling has to be done carefully with consideration of site-wide utilities and material balances.

1.5.5. PRES 2002

Smith (2002) highlighted the advantages of process integration for reduced environmental impact in his plenary lecture. He pointed out that Process Integration techniques have been extended beyond their original scope for solving energy problems to be able to address a wide range of process design issues.

Rodera *et al.* (2002, 2003) presented a contribution to process integration methodology for improving heat exchanger network operation. Their methodology featured a workflow to assist in the analysis of an existing heat exchanger network design when the operating conditions vary. It facilitated the involvement of the engineer in the daily operation and maintenance of the network.

Thonon (2002) presented the development and integration of advanced heat exchangers. The work covered the high performance heat exchangers in process integration. Particularly in distillation columns design, it is possible to achieve simultaneously improved controllability and energy savings.

A method to target the optimal integration of the utility system was demonstrated by Maréchal and Kalitvzenzeff (2002, 2003). They addressed multi-period optimisation incorporating models for selecting and targeting the optimal operation strategy of the utility system. This included gas turbines, steam network and cooling system together with the calculation of the optimal heat recovery system.

Václavík (2002, 2003) studied pressure as another parameter of the composite curves in heat integration. An important attempt has been made to evaluate the importance of pressure in heat integration.

Cost estimation can have a major impact on project profitability. Taal *et al.* (2002, 2003) provided a summary of the common methods used for cost estimation of heat exchange equipments and the sources of energy price projections. It shows the relevance of the choice of the right method and a reliable source of energy price forecast used when choosing between alternative retrofit projects or when trying to determine the viability of a retrofit project.

1.5.6. PRES'03

An important extension of process integration methodology: total site was applied by Sorin and Hammache (2003) in a new thermodynamic model for shaftwork targeting. A modified Site Utility Grand Composite Curve (SUGCC) diagram was proposed. The new model allows targeting fuel consumption, cooling requirement, and shaftwork production with high accuracy and visualising them directly as special segments on the T-H diagram.

The concept of thermal integration of trigeneration systems was presented by Teopa Calva *et al.* (2005). They addressed a further extension of the cogeneration. The use of the thermodynamic model helps to simulate the main components of the system and permits a fast and interactive way to design the optimum trigeneration scheme using the performance data of commercial gas turbines.

Lavric *et al.* (2003, 2005) presented the benefits and drawbacks of energy integration through virtual heat exchanges. The features of the proposed Reactors Energy Integration were illustrated by a case study, a two-bed methanol synthesis heat integrated reactor.

Brown *et al.* (2003, 2005) have combined Pinch Analysis, exergy analysis, and optimisation techniques to define energy targets at pulp and paper industry expressed in terms of the energy costs rather than energy requirements. The dual representation of thermodynamic and technological energy requirements can be a valuable tool for the early stages of process energy analysis.

Process integration approach was extended to water network design. Foo *et al.* (2003, 2005) applied the water pinch analysis to synthesise maximum water recovery networks for batch processes. A new numerical technique, time-dependent water cascade analysis was demonstrated. This new network representation has an advantage of clearly depicting the time-dependent nature of a batch water network.

Majozi (2003, 2005) presented an effective technique for wastewater minimisation in batch processes by formulation of a MINLP mathematical model approach. This water integration work minimised wastewater production through the implementation of numerous recycle and reuse opportunities.

An extended Pinch Technology was proposed by Zhelev (2003, 2005a) to deal with water and energy management. The application of the methodology is designed to achieve water

conservation through minimisation of evaporation losses. Its significance was demonstrated through case studies of a power station, a brewery, and a tissue factory.

1.5.7. PRES 2004

Kaggerud *et al.* (2006) suggested a new avenue of process integration combined with chemical integration. Process and chemical integration is proposed as an option to increase the overall efficiency as co-production of power and chemicals is utilised. Chemical and process integration can give economy of scale savings, better utilisation of the raw materials, improved energy efficiency and savings in investment costs.

Another heat integration contribution was presented by Anantharaman *et al.* (2006). Pinch Analysis, Exergy Analysis and Optimisation have all been used independently or in combination for the energy integration of process plants.

Cziner *et al.* (2005) addressed the potential of multi-criteria, decision-making performance in plant design with the aid of process integration. A hierarchical decision-making methodology was presented, where the environmental and safety regulations and the growing demand of consumers for higher product quality are included. The case study had a calcination kiln, followed by flue gas cleaning and heat recovery systems

The Pinch principle was further extended by Zhelev (2005b) in the opportunities to improve profits and reduce the investment cost through integrated management of resources such as electrical energy, steam and fresh water. Cost Composite Curves were created to target the optimum profitability to guide the decision making process in the context of key trade-offs. A Grid diagram analogy was used to show the money flow that can ensure meeting the targets.

1.5.8. PRES'05

Based on Pinch Analysis, a procedure was proposed by Markowski *et al.* (2005, 2007) for minimising the compressor shaft work in the refrigeration system. They studied the thermal separation of hydrocarbon mixtures in a sequence of heat-integrated distillation columns coupled with a refrigeration system via a heat exchanger network.

An automated approach for heat integration was presented by Moodley *et al.* (2005). They used a superstructure and mathematical model to demonstrate the optimum cooling water supply to a network of heat exchangers supplied by multiple sources.

The concept of comprehensive process integration was introduced by Hurme *et al.* (2005). It was defined as design, operation and management of industrial processes with system-oriented and integrated methods, models, and tools.

Mascia *et al.* (2005, 2007) presented an industrial case study on a design of heat integrated distillation systems for a light ends separation plan. They explored the synthesis of partially thermally coupled and heat-integrated distillation systems applied to the light ends separation section of a crude distillation plant. This distillation system employs the thermal coupling and the heat-integration principles to significantly reduce the heat requirements compared with the traditional simple column train.

1.5.9. PRES 2006

Picón-Núñez *et al.* (2007) studied the effect of the configuration of cooling networks on the total exchanger area. The chosen methodology combined the pinch design method based on vertical heat transfer and the minimum water use design method. A case study

demonstrated the methodology showing a practical approach to reduce operating costs in existing systems.

An extended pinch analysis and design procedure evaluating pressure based exergy for subambient cooling were presented by Aspelund *et al.* (2007). They demonstrated substantial potential for minimising energy requirements (total shaftwork) in subambient processes. The compression and expansion work is optimized for the process streams, together with the work needed to create necessary cooling utilities.

Panjeshahi and Tahouni (2008) presented the method of Pressure Drop Optimisation in Debottlenecking of HENs. Their method had been effectively applied in a case study involving the retrofit of a crude oil pre-heat train after increasing throughput. The debottlenecking of heat exchanger networks using optimum pressure drops would be able to predict the required additional heat recovery area with acceptable accuracy.

Lior (2007) reviewed the status and prospects of using fossil, nuclear and renewable energy use for power generation (including hydrogen, fuel cells, micropower systems, and the futuristic concept of generating power in space for terrestrial use). He summarized the promising energy R&D areas, their potential, foreseen improvements, their timescale, and latest trends in government funding.

1.5.10. PRES'07

The Pinch Technology was extended to CO₂ minimisation. Foo *et al.* (2007, 2008) demonstrated a Cascade Analysis Technique for Carbon and Footprint-Constrained Energy Planning. They presented algebraic targeting techniques for energy sector planning with carbon (CO₂) emission and land availability constraints.

Cirilly and Zhelev (2007, 2008) presented the pinch analysis for CO₂ emissions targeting and planning. The two main adaptations/extensions are the forecasting adaptation and the extension that accounts for the dynamic nature of electricity supply–demand.

Amann *et al.* (2007) presented the conversion of a natural gas combined cycle power plant using an advanced gas turbine for CO₂ pre-combustion capture. CO₂ recovery rate has a big impact on the power plant efficiency since a lot of steam is required to lower the low heating value (LHV) of the synthesis gas leaving the recovery process, thus reducing NO_x.

Perry *et al.*, (2007, 2008) extended the total site approach to integrate waste and renewable energy to reduce the carbon footprint of locally integrated energy sectors. This novel method can be successfully applied to integrate renewables into the energy source mix and consequently reduce the CFP of these locally integrated energy sectors.

Liebmann *et al.* (2007) evaluated different scenarios of bioethanol production with innovative energy supplying facilities. They studied the options for renewable energy supply such as biogas CHP and biogas boiler. This gave a good started to the integration of renewable energy into regional energy supply.

Foo *et al.* (2008) paid attention to heat integration in batch processes. Their work covered the minimum units targeting and network evolution for batch HENs. The minimum unit target sets the lower bound for a batch HEN prior to the network evolution, which is used to evolve the network to reduce its complexity. They have shown that to simplify a batch HEN with network evolution techniques, a thorough analysis has to be performed across all time intervals of the batch process. Two examples illustrated the applicability of the proposed techniques. Further work is envisaged by them to incorporate the targeting and evolutionary techniques into a rigorous optimisation model.

1.5.11. PRES 2008

Kelemen and Kenessey (2008) shared their experience, how to turn hydrocarbon molecules into financial benefits in the PRES 2008 plenary lecture. A profit-driven optimisation is presented. Process integration and supply chain management are the main steps to tackle the process cost, production capability and market demand.

Huising (2008) discussed the issues from climate change. Energy saving is one of the important steps to reduce the CO₂ emissions. He showed that process integration can benefit far beyond process design and synthesis.

Klemeš and Varbanov (2008) presented a further extension of the concepts of Total Sites (Klemeš *et al.*, 1997) and Locally Integrated Energy Sectors (Perry *et al.*, 2008). They added the integration of renewable energy sources into the problem scope, emphasising the variability of both user demands and the renewables availability.

Sustainability analysis has been a major consideration in the process synthesis. Sikdar (2008) presented a framework for sustainability analysis to evaluate the data, leading one to a decision to accept, reject or re-work a solution.

Morrison *et al.* (2008) presented an interesting application of solar thermal energy utilisation in food industry. They proposed to use captured solar heat in a way similar to heat pumping, thus upgrading waste heat flows to temperatures suitable for process use.

The Processes Integration concept has been extended to renewable energy supply chain synthesis by Lam *et al.* (2008, 2009) to assessing the feasible ways for transferring energy from renewable sources to customers in a given region. The studied region is partitioned into a number of clusters by using the developed Regional Energy Clustering (REC) algorithm. The energy planning and management is extended and illustrated in Regional Resource Management Composite Curve (RRMCC). It provides straightforward information of how to manage the surplus resources - biomass and land use in the region.

Desai and Bandyopadhyay (2008) proposed a scheme for efficient utilisation of lower-grade waste heat for power generation, using Organic Rankine Cycles. They provided a graphically assisted procedure for integrating an industrial process with an ORC thus efficiently reducing the process cooling demand and the need for external power import.

Ghajar and Tang (2008) presented the validity and limitations of the numerous two-phase non-boiling heat transfer correlations. The study presented a good opportunity for heat integration. It should be continued into advanced process integration steps.

1.6. Future Trends – Innovations in Energy, Resource and Footprint Targeting

Recent research has been expanding the scope of Process Integration as well as the performance criteria for the system evaluation.

1.6.1. Energy planning using carbon footprint

Climate change has been growing in importance to the international community. Most of the attention has been focused on the carbon footprint (CFP) as a measure of the extent of greenhouse gas emissions impact. An interesting contribution by Foo *et al.* (2008) dealt with the “Carbon and Footprint-Constrained Energy Planning Using Cascade Analysis Technique”. They presented algebraic targeting techniques for energy sector planning with CO₂ emission and land availability constraints. It is desirable to maximise the use of low carbon energy sources to reduce CO₂ emissions. This contribution provides an extension of the classic Pinch Analysis (Linnhoff and Hindmarsh, 1983) for identifying the minimum

amount of low- or zero-carbon energy sources needed to meet the national or regional energy demand, while not violating the CO₂ emission limits.

1.6.2 Extending Total Sites

An important innovation in the field of energy targeting and integration has been presented by Perry *et al.* (2008). This was a result of collaboration between the UK and Hungary under FP6 EC supported projects. The work presented an extension of the Total Site concept. Traditionally, Total Site meant only a set of industrial processes. This paper made another major step further by including commercial and residential energy users into the Total Site scope. The resultant process collections are termed Locally Integrated Energy Sectors. The method can be successfully applied to integrate renewables and consequently reduce the CFP of these locally integrated energy sectors.

1.7 Interesting Case Studies

1.7.1 PRES'03

A case study of pinch analysis was presented by Wising *et al.* (2005). They evaluated the potential for reducing the water and energy consumption by using pinch analysis approach. An existing pulp and paper mill was studied targeting the reduction of water consumption.

1.7.2. PRES 2004

A method for analysing energy, environmental, and economic efficiency for an integrated steel plant was presented by Larsson *et al.* (2006). Global mathematical models for steel making processes have been developed with the help of Process Integration techniques. The traditional beet sugar manufacturing technology has a considerable detrimental impact on the environment. Vaccari *et al.* (2005) gave an overview of the environmental problems in beet sugar processing. They applied Water Pinch and Thermal Pinch Analyses to assist in finding ways to drastically reduce both water and energy consumption.

1.7.3. PRES 2006

Process integration was applied to food industry. Kapustenko *et al.* (2008) demonstrated the integration of a heat pump into the heat supply system of a cheese production plant in Ukraine. They analysed a cheese production plant and the opportunity of heat integration of an existing refrigeration unit into the process considered.

1.7.4. PRES'07

A very interesting application of Heat Integration of evaporators with the remaining process has been presented by Axelsson *et al.* (2008). Their observation was that significant energy savings can be made in the pulp and paper industry by implementing process integrated evaporation (termed "PIvap"). Using pinch tools they found a solution where 1.3 GJ/Air Dried tonne of pinch violations were solved and 1.1 GJ/ADt of excess heat saved. Pulp-and-paper Kraft mills feature significant energy demands. Savulescu and Alva-Argaez (2008) have proposed a Process integration methodology to systematically address direct heat transfer (DHT) aspects in the Kraft mill energy system retrofit context. Their observation shows that energy-efficient nonisothermal mixing points should be located at the end of a stream. From the process perspective, mixing should be below pinch or above to eliminate the inefficiencies, due to DHT cross-pinch. Additionally, mixers located away from the pinch represent degrees of freedom to design an optimal heat transfer network.

1.7.5. PRES 2008

Levasseur *et al.* (2008) have presented an application of classical heat integration techniques with process changes to liquor evaporation in pulp-and-paper mill. The system involves multi-effect evaporation. The considered modifications were reduction of ΔT_{\min} , as well as variation of the pressures of evaporation effects. As a result, energy savings of up to 20 % were reported. Accounting for the non-continuous operation of pulp-and-paper mills, Morrison *et al.* (2008b) presented a case study for varying paper grades. They applied the Time Slice Model for Batch Heat Integration.

A powerful tool, Site-Model, was introduced by Hirata *et al.* (2007). To handle the trade-off between the flexibility and the interactions, all units should be managed simultaneously. The tool implements a large-scale MILP model for the utility system optimisation.

Nordgren *et al.* (2008) presented heat balancing study of a metallurgical process with the aim to perform a subsequent Heat Integration project. The paper is a part of a project which aim is to develop a process integration model for the Swedish iron ore company LKAB's production system in Malmbärg. The authors analyse the various processing zones of the furnaces and the opportunities for heat recovery using external heat exchangers.

2. Optimisation for Energy Savings and Reduced Emissions

The field is enormously wide. Therefore, this short overview is targeting optimisation methodologies which have the strongest impact on energy saving and pollution reduction.

2.1. Integrated Synthesis of Process and Heat Exchanger Networks

Nagy *et al.* (2001) developed a new algorithmic method for the integrated synthesis of process and heat exchanger networks. Different methods exist for algorithmic process-network synthesis (PNS) as well as for heat-exchanger-network synthesis; nevertheless, they cannot easily be integrated for number of reasons. For instance, the flow rates of streams are not specified a priori in PNS; in contrast, the flow rates and temperatures of hot and cold streams must be known as inputs in HENS. This difference can be attributed to the fact that the former is macroscopic in nature, while the latter is mesoscopic in nature; this gives rise to the characteristic differences between them. Moreover, both PNS and HENS inevitably encounter combinatorial complexity. Naturally, such complexity will magnify profoundly when they are integrated due to their interactions.

The P-graph framework developed earlier for PNS (Friedler *et al.*, 1992) has been extended to the integrated synthesis of process and heat-exchanger networks. This new method resorts mainly to hP-graphs adapted from the P-graphs in conjunction with the appropriate selection of inherent intervals of temperature range. Therefore, it focuses on the establishment of an appropriate technique for the integration of PNS and HENS (Nagy *et al.*, 2001). The resultant technique is largely based on combinatorial algorithms. The efficacy of the proposed approach is illustrated by the solution of an industrial problem.

2.2. Heat Integration in Batch Scheduling

Adonyi *et al.* (2003) developed a new algorithmic method for heat integration of batch processes. By nature, batch process scheduling and heat integration are two significantly different highly complex optimization problems. Many algorithmic and heuristic based methods exist for solving heat integration problems by resorting to Pinch Technology, superstructure based mixed integer programming, and integration with process network

synthesis. These methods have been developed for continuous processes where scheduling is obviously of no concern.

In principle, these two different problems can be solved sequentially, i.e., solving scheduling first and then heat integration or vice versa. Since the solution of one of them influences the other, the result of this simplistic approach is usually very poor. Consequently, an integrated consideration of scheduling and heat integration may provide appropriate solution. Since no method known up to that time for solving the integrated model, the development of a new method was desired for effective design and operation of batch processes. The main issue was how to operate tasks with potential heat exchange simultaneously without sacrificing the quality of the solution of scheduling. The proposed procedure is based on the branch-and-bound framework, where two optimization problems, the scheduling and the heat integration one, are considered simultaneously instead of consecutively.

2.3. Batch Scheduling with Minimising Cleaning Costs

The cleaning issue of batch processes, especially, paint production systems have been examined by Adonyi *et al.* (2008). Due to the large variety of options offered to customers, batch production schemes are highly accepted in paint industry implying that scheduling plays an important role in optimal allocation of plant resources among multiple products. Since in a batch process, the cleaning of equipment units is the major source of waste, waste minimization is also to be taken into account in determining the schedule. In the paint production, a product is produced by four successive tasks: grinding, mixing, storing the intermediate materials, and packing. Grinding, mixing and storing are batch type operations while packing is continuous.

A task cannot be performed by a dedicated equipment unit, because there are usually more tasks than equipment units. An equipment unit is assigned to each task for a time interval where the length of the interval must not be shorter than the processing time of the related task. Changeover time is defined for an equipment unit if cleaning is necessary. The whole amount of the intermediate material is used by the successive tasks. Traditionally, such assignment of equipment units to tasks and schedule of tasks is generated that have minimal makespan. This schedule provides the highest efficiency of the production system with the possibility of unnecessarily large waste generation. For determining the schedule of tasks that requires minimal cleaning cost, the objective function of the problem has to be modified. While in the original problem the makespan, in the reformulated problem the cleaning cost must be minimised. This reformulation has minor effect on the solution procedure. Therefore, an effective solver for the original problem is useful for the reformulated problem also.

The formerly developed S-graph framework (Romero *et al.*, 2004) proved to be highly effective in solving multipurpose batch scheduling; it has been specialised by Adonyi *et al.* (2008) for solving paint production scheduling problems including waste minimisation. The efficiency of the new approach is illustrated with the solution of large-scale paint production scheduling problems.

2.4. Strategic roadmap - Decomposition vs. Integration for process optimisation

PRES'03, held together with the 53rd Canadian Chemical Engineering Conference marked an important milestone in the development of the process optimisation field. The decomposition principle in process design has been used by researchers since the 1970's –

e.g. (Sirola, 1970). Friedler and Fan (2003) drafted a strategic roadmap for the development of process optimisation, analysing the interactions between the decomposition and integration principles. They have identified a number of threats to the optimality and feasibility of the process designs when applying decomposition and suggested measures to counteract the problems, centred around the concept of the integration of the methodologies for the component design problems.

This concept has revealed the need for algorithmic generation of the component models and the necessary interfaces enabling the interactions of the models and methods. The algorithmic generation of the models allows mainly ensuring their validity and completeness of the network superstructures. One efficient way for algorithmic model generation is using P-graph (Friedler *et al.*, 1992; Friedler *et al.*, 1993; Friedler *et al.*, 1995).

2.5. Looking Inside the Processes – Process Intensification

Reay (2008) has presented the role of process integration and intensification in cutting greenhouse gas emissions. He identified the challenges that intensification is able to meet across a range of sectors of industry and commerce as they relate to greenhouse gas control. He mentioned that the possibility of increased local production and the growing use of biological renewable feedstock open up new challenges and opportunities for those active in integration as well as intensification. He stated that between 1900 and 1955 the average rate of global energy use rose from about 1 TW to 2 TW. However, between 1955 and 1999 energy use rose from 2 TW to about 12 TW. To 2006, a further 16 % growth in primary energy use was recorded world-wide. The conclusions are that process intensification, although yet to fully emerge as an established technology in the process industries, offers significant opportunities for carbon reductions in sectors ranging from chemicals to food and glass manufacture.

2.6. Contributions from PRES Conferences

2.6.1. PRES'98

Heat integration of chemical multipurpose batch plants was studied by Sanmarti *et al.* (1998) based on directed graphs and exploiting the optimisation power of combinatorics. This approach has been further developed by Sanmarti *et al.* (2002) into S-graphs.

2.6.2. PRES'99

The problem of HENs flexibility and operability had been dealt with by Tantimuratha *et al.* (1999). They proposed simple MILP models to solve the problem. However, a closer combination with pinch analysis had still to come.

2.6.3. PRES 2000

Nagy *et al.* (2000, 2001) presented an algorithmic approach for integrated synthesis of process and heat exchanger networks. This work focused on the establishment of an appropriate technique for the integration of PNS and HENS. The resultant technique was largely based on combinatorics and combinatorial algorithms. This novel approach opened a new opportunity of the process integration approach.

2.6.4. PRES'01

Halasz *et al.* (2001, 2002) presented a novel tool, especially important for the retrofit design. An optimal design and operation of an existing steam-supply system of a chemical complex was demonstrated. The method developed is based on the P-graph, the decision-mapping, combinatorial algorithms, and the accelerated branch-and-bound method.

2.6.5. PRES 2002

Adonyi *et al.* (2002, 2003) introduced a novel S-graph approach to incorporate heat integration in batch process scheduling. The proposed procedure is based on the branch-and-bound framework, where two optimisation problems, the scheduling and the heat integration one, are considered simultaneously instead of consecutively.

2.6.6. PRES'03

Varbanov *et al.* (2005) proposed a method to synthesise industrial utility systems capable of cost-effective decarbonisation. It is based on improved models of utility equipment components and on an improved model and procedure for optimal synthesis. The environmental impact of utility systems was integrated into a synthesis model, which is dictated by the need for significant reduction of CO₂ emissions.

Application of pinch technology is presented by Ravagnani *et al.* (2005) to synthesise a HEN. A strategy for the synthesis and optimisation of heat exchanger networks was developed using genetic algorithm.

Synthesis of HEN by using mathematical model approach was presented by Markowski *et al.* (2003, 2005). Heat exchanger cleaning is postulated to maximise the avoided loss understood as the value of energy recovered if cleaning the HEN, minus the value of energy recovered without HEN cleaning, minus the cost of HEN cleaning. The mathematical formulation of the avoided loss is given and the computational approach to its maximisation is outlined.

2.6.7. PRES 2004

Ullmer *et al.* (2005) presented the methodology and software for the synthesis of process water systems. They developed an integrated strategy for the design of industrial process water systems to determine the optimal cost network, taking into consideration multiple contaminants and various possibilities of water reuse and regeneration. The efficiency and applicability of the software was demonstrated on a process water system of an oil refinery.

2.6.8. PRES'05

Hugo *et al.* (2005) presented a multi-objective optimisation model for strategic hydrogen infrastructure planning. The optimisation is conducted in terms of both investment and environmental criteria, with the ultimate outcome being a set of optimal trade-off solutions representing conflicting infrastructure pathways. This model had considerable potential, especially into the regional energy integration.

Ponton (2005) shared the experience on how to use the web based distance learning programme for continuing professional development in the control, modelling, and optimisation courses.

Transformation of process data into a meaningful description is very important to process integration. Drahoš and Růžička (2005) studied the characterization of process data such as pressure, temperature, and concentration by using time series analysis.

Dalaouti and Seferlis (2005) demonstrated the Orthogonal Collocation on Finite Elements (OCFE) modelling techniques for the design optimisation and dynamic simulation of complex distillation and absorption processes. This has been very important work in the field which still deserves more research.

2.6.9. PRES 2006

Pistikopoulos (2006) gave an overview of the mathematical foundations of multi-parametric programming for advanced models. He also presented the application of model-based optimal control with emphasis on how to design off-line affordable advanced parametric controllers for chemical processes.

Majozzi (2006) demonstrated a continuous-time mathematical formulation for optimisation of heat integrated batch chemical plants. This formulation is applicable to both multipurpose and multiproduct facilities in which opportunities for direct heat integration exist. A literature example and a case study were tackled.

2.6.10. PRES'07

Friedler and Varbanov (2007, 2008) presented an application of the CHP concept in combination with the P-graph framework for designing complex systems for energy supply and conversion. Two kinds of High-Temperature Fuel Cells (HTFC) were considered – Molten Carbonate Fuel Cells (MCFC) and Solid Oxide Fuel Cells (SOFC). The paper presents a tool for the evaluation of energy conversion systems involving Fuel Cell Combined Cycles (FCCC) subsystems, utilizing biomass and/or fossil fuels. This task involves significant combinatorial complexity, efficiently handled by the P-graph algorithms, producing cost-optimal FCCC configurations. It also accounts for the carbon footprint of the various technology and fuel options. The results show that such systems employing renewable fuels can be economically viable for a wide range of economic conditions, mainly due to the high energy efficiency of the FC-based systems, having the potential to reduce the carbon footprint of energy supply by 50 to 75 %.

2.6.11. PRES 2008

Tan (2008) presented an accelerated modification of the popular Simulated Annealing optimisation algorithm employing swarm intelligence techniques. Two modified SA algorithms have been developed by incorporating parallel searching and information sharing features found in swarm-based techniques such as PSO and SFLA, as well as an adaptive cooling schedule. Tests on three chemical process network design and synthesis problems showed that the modifications yield improvements in search characteristics as compared to conventional SA and other optimisation algorithms. The new algorithms needed fewer function evaluations to reach the final solution and gave more robust and consistent results when tested repeatedly for the same problem.

An approach to multiperiod HEN synthesis using Simulated Annealing (Ahmad *et al.*, 2008) has been suggested. It uses a completely evolutionary strategy starting from a trivial network topology connecting all hot streams to coolers and all cold streams to heaters. They stated that the performance of the optimisation procedure is comparable to the

existing Mathematical Programming based ones. The method does not rely on any superstructure, is not subject to decomposition of the main problem, and can explore a greater search area, increasing the probability of obtaining the global optimum.

3. Conclusions and future outlook

Modern societies must face numerous issues in seeking to secure a sustainable energy supply, reduce climate changes, and ensure food production. The rapid increase in global energy consumption makes the problem more complicated. Recent oil and gas crises have shown the vulnerability of the societies in terms of climate changes and energy supplies. However, due to the complexity of the global challenges, it can be realised that each person or team has limits to the issues that they could effectively address. This is the reason why this plenary is based upon the specialised inputs from a number of world-leading scientists and technologists. Taken as a whole, the reviewed papers address many of the challenges pertaining to global climate change and to the impacts of the decisions that can be made.

Although, new insights are emerging on some energy-related problems, which seem to be rather straightforward, most of them have not yet been satisfactorily solved. Many of the problems have been addressed annually at the PRES conferences held during the last 12 years. The following issues should be further explored in the future:

- Diversification of energy sources and supply chains
- Mass storage of energy (especially of electricity and heat)
- Change of the societal approach away from wasting energy.
- Sustainable energy generation
- Securing fresh water for the world's growing human population.

The list could be considerably extended. It is a positive sign that some of the big players are researching these issues see e.g. (SHELL, 2008). However, much more collaboratively orchestrated work is needed to find proper answers to these challenges. The PRES series of conferences has been designed to provide the necessary forum and networking opportunities for accelerating the scientific and engineering progress in the field.

References

- Aaltola J., 1999, Use of process heat of a paper integrate in the district heating systems of two cities. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 95-100.
- Adonyi R., Biro G., Holczinger T. and Friedler F., 2008, Effective scheduling of a large-scale paint production system, *Journal of Cleaner Production* 16 (2), 225-232.
- Adonyi R., Romero J., Puigjaner L. and Friedler F., 2002, Incorporating heat integration in batch process scheduling, CHISA 2002 Proceedings, Set 4, PRES 2002, I 6.5.
- Adonyi R., Romero J., Puigjaner L. and Friedler F., 2003, Incorporating heat integration in batch process scheduling, *Applied Thermal Engineering* 23, 1743-1762.
- Ahmad M. I., Chen L., Jobson M., Zhang N., 2008, Synthesis and optimisation of heat exchanger networks for multi-period operation by simulated annealing, CHISA 2008 Proceedings, Summaries 4, PRES 2008, ,ČSCHI, K2.2, 1511.

- Al-Riyami B.A., Klemeš J., Perry S., 2000, Heat integration retrofit analysis of a heat exchanger network of a fluid catalytic cracking plant. CHISA 2000 Proceedings, Set 4, PRES 2002, Prague, P 7.60 [1147]
- Al-Riyami B.A., Klemeš J., Perry S., 2001, Heat integration retrofit analysis of a heat exchanger network of a fluid catalytic cracking plant, Applied Thermal Engineering 21, 1449 – 1487
- Alves J., 1999, Analysis and design of refinery hydrogen distribution systems, PhD Thesis, UMIST, Manchester, United Kingdom.
- Anantharaman R., Abbas Own S. and Gundersen T., 2006, Energy level composite curves—a new graphical methodology for the integration of energy intensive processes, Applied Thermal Engineering 26, 1378–1384.
- Asante N.D.K. and Zhu X.X., 1996, An automated approach for heat exchanger network retrofit featuring minimal topology modifications. Computers Chemical Engng 20(Supplement), S7–S12.
- Aspelund A., Berstad D.O. and Gundersen T., 2007, An extended pinch analysis and design procedure utilizing pressure based exergy for subambient cooling, Applied Thermal Engineering 27, 2633–2649.
- Assadi M., Johansson K.B., 1999, Applying pinch method and exergy analysis to BIO-IGHAT power plant. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 139-144.
- Axelsson E., Marcus R., Olsson M.R. and Berntsson T., 2008, Opportunities for process integrated evaporation in a hardwood pulp mill and comparison with a softwood model mill study, Applied Thermal Engineering 28 (16), 2100–2107.
- Bébar L., Martinak P., Hájek J., Stehlík P., Hajny Z. and Oral J., 2002, Waste to energy in the field of thermal processing of waste, Applied Thermal Engng 22, 897–906.
- Bébar L., Martinak P., Hájek J., Stehlík P., Hajny Z. and Oral J., 2001, Waste to energy in the field of thermal processing of waste, 4th PRES'01, Florence, AIDIC, 453- 458.
- Bochenek R., Jezowski J. and Jezowska A., 1998, Retrofitting Flexible Heat Exchanger Networks – Optimization vs. Sensitivity Tables Method, CHISA'98 / 1st Conference PRES'98, Prague, F1.4 [985]
- Brown D., Maréchal F. and Paris, J., 2003, Cogeneration system design methodology in pulp and paper process, 53th CSChE 2003 with PRES' 03, Hamilton, Canada, 343.
- Brown D., Maréchal F. and Paris, J., 2005, A dual representation for targeting process retrofit, application to a pulp and paper process, Applied Thermal Engineering 25 (7), 1067–1082
- Burianec Z, Mařík K. and Klemeš J., 1999, HENCOCODES - Hocserelehalozat irányítás-tervezés segítő szakértői rendszer (HENCOCODES- An Expert System for Designing the Control of Heat-Exchangers Networks). Magyar Kemikusok Lapja, 54(1) 22-29, (*in Hungarian*).
- Cirilly D. and Zhelev T., 2007, Current Trends in emissions targeting and planning—an application of CO₂ emissions pinch analysis to the Irish electricity generation sector, PRES' 07, ed. Jiří Klemeš, Chemical Engineering Transactions, 12, 91 – 97.
- Cirilly D. and Zhelev T., 2008, Current trends in emissions targeting and planning—an application of CO₂ emissions pinch analysis to the Irish electricity generation sector, Energy 33, 1498–1507.

- Cheung K-Y. and Hui C-W., 2004, Total-site scheduling for better energy utilization, *Journal of Cleaner Production* 12 (2004) 171–184
- Cheung K-Y. and Hui C-W., 2001. Total-site maintenance scheduling, *Proceedings of 4th Conference PRES'01*, ed. J. Klemeš, AIDIC, 355 – 363.
- Cziner K., Tuomaala M. and Hurme M., 2005, Multicriteria decisions making in process Integration, *Journal of Cleaner Production* 13, 475–483.
- Dalaouti N. and Seferlis P., 2005, Design and optimisation of complex separation process using orthogonal collocation on finite elements modelling techniques. *PRES'05*, ed. J. Klemeš, *Chemical Engineering Transactions* 7, 321-326.
- Desai N.B. and Bandyopadhyay S., 2008, Process integration of organic Rankine cycle, *CHISA 2008 Proceedings, Summaries 4*, *PRES 2008, ČSCHI*, 1244 – 1245.
- Dhole V.R. and Linnhoff B., 1993, Total site targets for fuel, co-generation, emissions and cooling, *Computers & Chemical Engineering*, 17 (Supplement), S101-S1.
- Dogru E., Ozkan S. and Bolat E., 1999, A heat exchanger networks design for an ammonium plant: A supertarget application, *PRES'99 Proceedings*, ed. F. Friedler and J. Klemeš, *Hungarian Chemical Society, Budapest*, 245-249.
- Drahoš J. and Růžička M.C., 2005, Time Series Analysis in Characterization of Process Data, *PRES'05*, ed. J. Klemeš, *Chemical Engineering Transactions* 7, 607- 613.
- El-Halwagi M. and Manousiouthakis V., 1989, Synthesis of Mass Exchange Networks, *AIChE Journal* 35 (8), 1233-1244.
- Foo D.C.Y., Chew Y.H. and Lee C.T., 2008, Minimum units targeting and network evolution for batch heat exchanger network, *Applied Thermal Engineering* 28 (16), 2089–2099.
- Foo, D.C.Y., Manan Z.A. and Tan L.Y., 2003, Synthesis of maximum water recovery network for batch process systems, *PRES'03/CSChE'03*, Hamilton, Canada, 81.
- Foo, D.C.Y., Manan Z.A. and Tan L.Y., 2005, Synthesis of maximum water recovery network for batch process systems, *Journal of Cleaner Production* 13, 1381–1394.
- Foo D.C.Y., Tan R.R. and Ng D.K.S., 2007, Target for minimum low and zero-carbon energy resources in carbon-constrained energy sector planning using cascade analysis, *PRES'07*, ed. J. Klemeš, *Chemical Engineering Transactions*, 12:139– 144.
- Foo, D.C.Y., Tan R.R. and Ng D.K.S., 2008. Carbon and footprint-constrained energy planning using cascade analysis technique, *Energy* 33, 1480–1488.
- Fraser D.M. and Hallale N., 1999, Systematic effluent reduction through pinch technology. *PRES'99 Proceedings*, ed. F. Friedler and J. Klemeš, *Hungarian Chemical Society, Budapest*, 281-286.
- Friedler F. and Fan L.T., 2003, Process design and operation: decomposition vs. integration, *PRES'03/CSChE'03*, Hamilton, Ontario, Canada.
- Friedler F. and Varbanov P., 2008, P-graph methodology for cost-effective reduction of carbon emissions involving fuel cell combined cycles, *PRES'07*, ed. Jiří Klemeš, *Chemical Engineering Transactions*, 12: 133 – 138
- Friedler F. and Varbanov P., 2008, P-graph methodology for cost-effective reduction of carbon emissions involving fuel cell combined cycles, *Applied Thermal Engineering* 28(16), 2020–2029.
- Friedler F., Tarjan K., Huang Y.W. and Fan L.T., 1992, Graph-theoretic approach to process synthesis: axioms and theorems, *Chem. Eng. Sci.* 47 (8), 1973-1988.

- Friedler F., Tarjan K., Huang Y.W. and Fan L.T., 1993, Graph-Theoretic Approach to Process Synthesis: Polynomial Algorithm for Maximal Structure Generation, *Comput. Chem. Eng.* 17 (9), 929-942.
- Friedler F., Varga J.B. and Fan L.T., 1995, Decision-Mapping: A Tool for Consistent and Complete Decisions in Process Synthesis, *Chem. Eng. Sci.* 50 (11), 1755-1768.
- Galli M.R. and Cerdá J., 1999, Synthesis of heat exchanger networks featuring a minimum number of bounded-size shells, *PRES'99 Proceedings*, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 293-298.
- Ghajar A. and Tang C.C., 2008, Importance of Non-Boiling Two-Phase Flow Heat Transfer in Pipes for Industrial Applications, *CHISA 2008 Proceedings, Summaries 4*, PRES 2008, Prague, ČSCHI, 1255- 1256.
- Gottschalk A., Janowsky R. and Nemecek M., 1999, Application of HEATPERT for the energy integration of industrial chemical processes. *PRES'99 Proceedings*, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 305-310.
- Grabowski M., Klemeš J., Urbaniec K., Vaccari G. and Zhu X.X., 2001, Minimum energy consumption in sugar production by cooling crystallisation of concentrated raw juice, *Applied Thermal Engineering* 21, 1319 – 1329.
- Grabowski M., Klemeš J., Urbaniec K., Vaccari G. and Zhu X.X., 2000, Minimum energy consumption in sugar production by cooling crystallisation of concentrated raw juice, *CHISA 2000, Set 4, PRES 2000, Prague, H 1.5* [1204].
- Gundersen T., 1998, Recent trends in Process Integration, Methods, Software and Applications, *CHISA'98 / 1st Conference PRES'98, Prague*, lecture F1.1 [1302].
- Halasz L., Nagy A.B., Ivicz T., Friedler F. and Fan L. T., 2002, Optimal retrofit design and operation of the steam-supply system of a chemical complex, *Applied Thermal Engineering* 22, 939–947.
- Halasz L., Nagy A.B., Ivicz T., Friedler F. and Fan L.T., 2001, Optimal retrofit design and operation of the steam-supply system of a chemical complex, 4th Conference, *PRES'01*, ed. J. Klemeš, Florence, AIDIC, 331 – 336.
- Hallale N. and Liu F., 2001, Refinery hydrogen management for clean fuels production, *Advances in Environmental Research* 6 (1), 81-98.
- Hashemi-Ahmady, A., Zamora J. M. And Gundersen, T., 1999. A sequential framework for optimal synthesis of industrial size heat exchanger networks. *PRES'99 Proceedings*, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 329-334
- Hassan M., Klemeš J. and Plešu V., 1998, Process integration analysis & retrofit suggestions for a FCC plant. *CHISA'98 / 1st Conference PRES'98, Prague, 1998*, lecture F7.4. [443]
- Hassan M., Klemeš J. and Plešu V., 1999, Process Integration Analysis & Retrofit Suggestions for A FCC Plant. *Integrirrovannye Tehnologii i Energoberegenie (Integrated Technologies and Energy Saving)*, 2, 10 – 30, ISBN-5-7763-2106-9 (*in Russian*).
- Hirata K., Chan P., Cheung K.-Y., Sakamoto H., Ide K. and Hui Ch.-W., 2007, Site-model utility system optimisation – industrial case study of KKEPC, *Applied Thermal Engineering* 27, 2687–2692.
- Hohmann E.C., 1971, *Optimum Networks for Heat Exchange*, PhD Thesis, University of Southern California, Los Angeles, United States.

- Hugo A., Rutter P., Georgiadis M.C. and Pistikopoulos E.N., 2005, A multi-objective optimisation model for strategic hydrogen infrastructure planning, PRES'05, ed. J. Klemeš, Chemical Engineering Transactions 7, 1-6.
- Huisingh D., 2008, Harbingers of Hope in the Transition to Sustainable Societies: Beyond Gloom and Doom to Action, CHISA 2008 Proceedings, Summaries 4, PRES 2008, Prague, ČSCHI, 1089 – 1090.
- Hurme M., Tuomaala M. and Ahtila P., 2005, Process efficiency by comprehensive process integration, PRES'05, ed. J. Klemeš, Chemical Engng Trans 7, 447 – 452.
- Kaggerud K.H., Bolland O. and Gundersen T., 2006, Chemical and process integration: synergies in co-production of power and chemicals from natural gas with CO₂ capture, Applied Thermal Engineering 26, 1345–1352.
- Kalitventzeff B., Maréchal F. and Closon H., 2000, Better solutions for process sustainability through better insight in process energy integration, CHISA 2000 Proceedings, Set 4, PRES 2000, Prague, H 1.1. [1240]
- Kalitventzeff B., Maréchal F. and Closon H., 2001, Better solutions for process sustainability through better insight in process energy integration, Applied Thermal Engineering 21, 1349 – 1368.
- Kalitventzeff B., Dumont M.-N. and Maréchal F., 1998, Process Integration Techniques in the Development of New Energy Technologies: Application to Isothermal Gas Turbine, CHISA'98 / 1st Conference PRES'98, Prague, F3.1 [447]
- Kapustenko P., Ulyev L., Boldyryev S. and Garev, A., 2008, Integration of a heat pump into the heat supply system of a cheese production plant, Energy 33, 882–889.
- Kelemen B. and Kenessey G., 2008, Profit-driven optimisation in the oil industry: How to turn hydrocarbon molecules into financial benefits. CHISA 2008 Proceedings, Plenary Lectures Summaries, ČSCHI, 9 – 11.
- Klemeš J. and Varbanov P., 2008, Total sites for combined utilisation of renewables and fossil fuels via improved energy conversion technologies. CHISA 2008 Proceedings, Summaries 4, PRES 2008, ČSCHI, 1242-1243.
- Klemeš J., Dhole V.R., Raissi K., Perry S.J. and Puigjaner L., 1997, Targeting and Design Methodology for Reduction of Fuel, Power and CO₂ on Total Sites, Applied Thermal Engineering 17 (8/10), 993-1003.
- Klemeš J., Kimenov G. and Nenov N., 1998, Application of pinch-technology in food industry. CHISA'98 / 1st Conference PRES'98, Prague, Lecture F6.6 [136]
- Klemeš J., Nenov N., Kimenov G. and Mintchev M., 1999, Heat Integration in Food Industry. *Integrirrovannye Tehnologii i Energosberegenie (Integrated Technologies and Energy Saving)*, 4, 1999, 9 – 26, ISBN-5-7763-2106-9 (*in Russian*).
- Klemeš J., Urbaniec K. and Zalewski P., 1999, Retrofit design for polish sugar factories using process integration methods. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 377-382
- Lam, H.L., Klemeš, J. and Varbanov, P., 2008. An efficient planning and implementation of regional renewable energy supply chain, CHISA 2008 Proceedings, Summaries 4, PRES 2008, ČSCHI, K2.2, 1218-1219.
- Lam, H.L., Varbanov, P and Klemeš, J., 2009. Minimising carbon footprint of regional biomass supply chains. *Resources, Conservation and Recycling*, doi:10.1016/j.resconrec.2009.03.009.

- Larsson M., Wang Ch. and Dahl J., 2006, Development of a method for analysing energy, environmental and economic efficiency for an integrated steel plant, *Applied Thermal Engineering* 26, 1353–1361.
- Lavric V., Baetens D., Plešu V., and De Ruyck J., 2002, Entropy generation reduction through chemical pinch analysis, *CHISA 2002/ PRES 2002 Proc, Set 4, H 5.6*.
- Lavric V., Baetens D., Plešu V., and De Ruyck J., 2003, Entropy generation reduction through chemical pinch analysis, *Applied Thermal Engineering* 23, 1837–1845.
- Lavric V., Plešu V. and De Ruyck J., 2003, Chemical reactors energy integration through virtual heat exchangers – benefits and drawbacks, *PRES'03/CSCHE'03, Hamilton, Canada*, 167.
- Lavric V., Plešu V. and De Ruyck J., 2005, Chemical reactors energy integration through virtual heat exchangers – benefits and drawbacks, *Applied Thermal Engineering* 25 (7), 1033–1044.
- Levasseur Z.P., Palese V. and Maréchal, F., 2008, Energy integration study of a multi-effect evaporator. *CHISA 2008 Proc, Summaries 4, PRES2008, ČSCHI, 1184-1185*.
- Liebmann B., Pfeffer M., Wukovits W., Bauer A., Amon T., Gwehenberger G., Narodslawsky M. and Friedl A., 2007, Modelling of small-scale bioethanol plants with renewable energy supply, *PRES'07, ed. J. Klemeš, Chemical Engineering Transaction* 12, 309-314.
- Linnhoff B. and Akinradewo, 1998, Automated Interface between Simulation and Integration, *CHISA 1998 / 1st Conference PRES 1998, Plenary lecture A3.0 [818]*
- Linnhoff B. and Flower J.R., 1978, Synthesis of Heat Exchanger Networks: I. systematic generation of energy optimal networks, *AIChE Journal* 24 (4), 633–642.
- Linnhoff B. and Hindmarsh E., 1983, The Pinch Design Method for Heat Exchanger Networks, *Chemical Engineering Science* 38 (5), 745-763.
- Linnhoff B., Mason D.R. and Wardle I., 1979, Understanding Heat Exchanger Networks, *Computers & Chemical. Engineering* 3 (1-4), 295-302.
- Linnhoff B., Townsend D.W., Boland D., Hewitt G.F., Thomas B.E.A., Guy A.R., and Marsland R.H., 1982, last edition 1994, *A User Guide to Process Integration for the Efficient Use of Energy*, IChemE, Rugby, UK
- Lior N., 2006, Energy resources and use: the present situation and possible paths to the future, *CHISA 2006 Proc, Summaries 4, PRES 2006, Prague, ČSCHI, 1151-1152*.
- Lior N., 2008, Energy resources and use: the present situation and possible paths to the future, *Energy* 33, 842–857.
- Majozi T., 2003, An effective technique for wastewater minimisation in batch processes, *PRES' 03/ CSCHE'03, Hamilton, Canada*, 160
- Majozi T., 2005, An effective technique for wastewater minimisation in batch processes, *Journal of Cleaner Production* 13, 1374–1380.
- Majozi T., 2006, Heat integration of multipurpose batch plants using a continuous-time framework, *Applied Thermal Engineering* 26, 1369–1377.
- Maréchal F. and Kalitvenczeff B., 2002, Targeting the integration of multi-period utility systems for site scale process integration, *CHISA 2002 Proc, 4, PRES 2002, H 5.1*.
- Maréchal F. and Kalitvenczeff B., 2003, Targeting the integration of multi-period utility systems for site scale process integration, *Applied Thermal Engng* 23, 1763–1784.
- Mařík K., Klemeš J. and Jakeš B., 1998, Design Tool for Flexible and Energy Efficient HENs. *CHISA'98 / 1st Conference PRES'98, Prague, 1998, F5.2. [606]*

- Markowski M., and Urbaniec K., 2003, Optimal cleaning schedule for heat exchangers in a HEN, PRES' 03/ CSChE'03, Hamilton, Canada, 88.
- Markowski M. and Urbaniec K., 2005, Optimal cleaning schedule for heat exchangers in a heat exchanger network, Applied Thermal Engineering 25 (7), 1019–1032.
- Markowski M., 1999, Reconstruction of heat exchanger network under industrial constraints – the case of a crude distillation unit. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 439-444.
- Markowski M., Trafczynski M. and Urbaniec K., 2005, Energy expenditure in the thermal separation of hydrocarbon mixtures using a sequence of heat-integrated distillation columns, PRES'05, ed. J. Klemeš, Chemical Engng Transac 7, 73–78.
- Markowski M., Trafczynski M. and Urbaniec K., 2007, Energy expenditure in the thermal separation of hydrocarbon mixtures using a sequence of heat-integrated distillation columns, Applied Thermal Engineering 27, 1198–1204.
- Mascia M., Ferrara F., Vacca A., Tola G. and Errico M., 2005, Design of heat integrated distillation systems for a light ends separation plant, PRES'05, ed. J. Klemeš, Chemical Engineering Transactions 7, 151 – 157.
- Mascia M., Ferrara F., Vacca A., Tola G. and Errico M., 2007, Design of heat integrated distillation systems for a light ends separation plant, Applied Thermal Engineering 27, 1205–1211.
- Mavromatis S.P. and Kokossis. A.C., 1998, Conceptual Optimisation of Utility Networks for Operational variations – I. Targets and Level Optimisation. Chem. Eng. Sci., 53(8), 1585-1608.
- Moodley A. and Majoji T., 2005, Development of a unified mass and heat integration framework for sustainable design – An automated approach. PRES'05, ed. Jiří Klemeš, Chemical Engineering Transactions 7, 465 – 470.
- Morrison A.S., Atkins M.J., Walmsley M.R.W. and Riley J., 2008b, Non-continuous pinch analysis of a paper machine in an integrated kraft pulp & paper mill. CHISA 2008 Proceedings, Summaries 4, PRES 2008, ČSCHI, 1194 – 1195.
- Morrison A.S., Atkins M.R. and Walmsley M.R.W., 2008a, Integration of solar thermal for improved energy efficiency in low-temperature-pinch industrial processes. CHISA 2008 Proceedings, Summaries 4, PRES 2008, ČSCHI, 1097- 1098.
- Nagy A.B., Adonyi R., Halasz L., Friedler F. and Fan L.T., 2001, Integrated Synthesis of Process and Heat Exchanger Networks: Algorithmic Approach, Applied Thermal Engineering 21 (13-14), 1407-1427.
- Nagy A.B., Biros G., Friedler F. and Fan L.T., 2000, Integrated Synthesis of Combined Process and HENs, CHISA 2000, 4, PRES 2000, Prague, P7.71 [1204].
- Nordgren S., Lindblom B., Dahl J. and Wang C., 2008, Process integration in an iron ore upgrading process system – analysis of mass and energy flows within a straight grate induration furnace, CHISA 2008 Proc, 4, PRES 2008, ČSCHI, 1172 – 1173.
- Panjeshahi M.H. and Tahouni N., 2008, Pressure drop optimisation in debottlenecking of heat exchanger networks, Energy 33, 942–951.
- Papoulias S.A. and Grossmann I.E., 1983, A structural optimization approach in process synthesis. II: Heat recovery networks, Computers Chemical Engng 7 (6), 707-72.
- Perry S., Klemeš J. and Bulatov I., 2007, Integrating waste and renewable energy to reduce the carbon footprint of locally integrated energy sectors, PRES'07, ed. Jiří Klemeš, Chemical Engineering Transactions, 12, 593 – 598.

- Perry S., Klemeš J. and Bulatov I., 2008, Integrating waste and renewable energy to reduce the CFP of locally integrated energy sectors, *Energy* 33, 1489–1497.
- Picón-Núñez M., Morales-Fuentes A. and Vázquez-Ramírez E.E., 2007, Effect of network arrangement on the heat transfer area of cooling networks, *Applied Thermal Engineering* 27, 2650–2656.
- Pistikopoulos S., 2006, Parametric programming and control, CHISA 2006 Proceedings, Summaries 4, PRES 2006, Prague, ČSCHI, 1060.
- Plešu V., Klemeš J. and Georgescu M., 1998, Applications of Process Integration in Romanian Oil Refining and Petrochemical Industry, CHISA'98 / 1st Conference PRES'98, Prague, Lecture F6.7 [1130]
- Ponton J.W., 2005, Web based distance learning for CPD. PRES'05, ed. J. Klemeš, *Chemical Engineering Transactions* 7, 405-411.
- PRES Conference – Process Integration, Modelling and Optimisation for Energy Saving and Pollution Reduction < www.conferencepres.com > (24/04/2009)
- Raissi K., 1994, Total Site Integration. PhD Thesis, UMIST, UK.
- Ravagnani M.A.S.S., Silva A.P., Arroyo P.A. and Constantino A.A., 2003, Heat exchanger network synthesis and optimisation using genetic algorithm, PRES'03 /CSChE'03, Hamilton, Canada, 594
- Ravagnani M.A.S.S., Silva A.P., Arroyo P.A. and Constantino A.A., 2005, Heat exchanger network synthesis and optimisation using genetic algorithm, *Applied Thermal Engineering* 25 (7), 1003–1017.
- Reay D., 2007, The role of process intensification in cutting greenhouse gas emissions, PRES'07, Ischia - Italy, ed. Jiří Klemeš, *Chemical Engineering Trans.*, 12, 1 – 12.
- Reay D., 2008, The role of process intensification in cutting greenhouse gas emissions, *Applied Thermal Engineering* 28 (16), 2011–2019.
- Rodera H. and Bagajewicz M., 1999, Multipurpose heat exchanger networks for heat integration across plants, PRES'99 Proceedings, ed. F. Friedler and J. Klemeš Hungarian Chemical Society, Budapest, 547-552.
- Rodera H., Westphalen D.L. and Shethna H.K., 2002, A methodology for improving heat exchanger network operation, CHISA 2002, Set 4, PRES 2002, Prague, I 3.4.
- Rodera H., Westphalen D.L. and Shethna H.K., 2003, A methodology for improving heat exchanger network operation, *Applied Thermal Engineering* 23, 1729–1741.
- Romero J., Puigjaner L. Holczinger T. and Friedler F., 2004. Scheduling Intermediate Storage Multipurpose Batch Plants Using the S-Graph, *AIChE J.*, 50(2),403-417.
- Sadhukhan J. and Zhu X. X., 2001, Integration strategy of gasification technology: A gateway to future refining, PRES' 01, ed J. Klemeš, Florence, AIDIC, 31 – 36.
- Sanmanti E., Friedler F. and Puigjaner L., 1998, Heat Integration in Chemical Multipurpose Batch Plants Using Schedule-Graph Representation, CHISA'98/1st PRES'98 Prague, Lecture F2.1 [92]
- Sanmanti E., Holczinger T., Puigjaner L. and Friedler F., 2002, Combinatorial Framework for Effective Scheduling of Multipurpose Batch Plants, *AIChE Journal* 48 (11), 2557-2570.
- Savulescu L.E. and Alva-Argaez A., 2008, Direct heat transfer considerations for improving energy efficiency in pulp and paper Kraft mills, *Energy* 33, 1562–71.

- Seikova I., Varbanov P. and Ivanova E., 1999, Debottlenecking of a heat-integrated crude-oil distillation system. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš Hungarian Chemical Society, Budapest, 583-588.
- SHELL, Real Energy Worlds, www.realenergy.shell.co.uk/?lang=en_GB&page=homeFlash&access=false&site_version=flash#> (03/01/2009).
- Siirola J.J., 1970. The Computer-Aided Synthesis of Chemical Process Designs, PhD thesis, University of Wisconsin, USA.
- Sikdar S.K., 2008, Chemical process sustainability and applicable metrics, CHISA 2008 Proceedings, Summaries 4, PRES 2008, Prague, ČSCHI, 1117 – 1118.
- Smith R., 1999, State of the art in process integration, PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 15-21.
- Smith R., 2002, Process integration for reduced environmental impact, CHISA 2002 Proceedings, Set 4, PRES 2002, Prague, H 2.1.
- Sorin M. and Hammache A., 2003, A new thermodynamic model for shaftwork targeting on total sites, PRES'03/CSCHE'03, Hamilton, Canada, 345.
- SuperTarget, V. 4.0, 1997, Linnhoff-March Ltd, Knutsford, UK.
- Taal M., Bulatov I., Klemeš J. and Stehlik P., 2002, Cost estimation and energy price forecasts for economic evaluation of retrofit projects, CHISA 2002 Proceedings, Set 4, PRES 2002, Prague, I 5.4.
- Taal M., Bulatov I., Klemeš J. and Stehlik P., 2003, Cost estimation and energy price forecasts for economic evaluation of retrofit projects, Appl Ther Eng 23, 1819-1835.
- Tan R.R., 2008, An adaptive swarm-based simulated annealing algorithm for process optimization, CHISA 2008 Proceedings, Sum 4, PRES 2008, ČSCHI, 1257 – 1258.
- Tantimuratha L., Antonopoulos D.K. and Kokossis A.C., 1999, Flexibility targets for HENs: Conceptual programming approach for grassroots and retrofit design. PRES'99 Proc, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 643-648.
- Teopa Calva E., Picón-Núñez M. and Rodríguez-Toral M.A., 2005, Thermal integration of trigeneration systems, Applied Thermal Engineering 25 (7), 973–984.
- Thonon B., 2002, Development of advanced heat exchangers and process control for high energy efficient distillation columns and separation processes, CHISA 2002 Proceedings, Set 4, PRES 2002, I 3.1.
- Tovazhyansky L.L., Kapustenko P.A., Uliev L.M., Perevertlenko A.Yu. and Chernyshov A.I., 1999, Application of process integration for energy saving and pollution reduction in Ukraine. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 659-664.
- Townsend D.W. and Linnhoff B., 1983, Heat and power networks in process design. Part II: Design procedure for equipment selection and process matching, AIChE Journal 29 (5), 748 – 771.
- Ullmer C., Kunde N., Lassahn A., Gruhn G. and Schultz K., 2005, WADO™: Water design optimisation - software for the synthesis of process water systems, Journal of Cleaner Production 13, 485 – 494.
- Umeda T., Harada T. and Shiroko K.A., 1979, Thermodynamic Approach to the Synthesis of Heat Integration Systems in Chemical Processes, Computers Chemical Engineering, 3, 273-282.

- Umeda T., Itoh J. and Shiroko K., 1978, Heat Exchange System Synthesis, Chem. Eng. Prog. 74 (7), 70-76.
- Vaccari G., Tamburini E., Sgualdino G., Urbaniec K. and Klemeš J., 2005, Overview of the environmental problems in beet sugar processing, J of Clean. Prod. 13, 499-507.
- Václavek V., Novotná A. and Dedková J., 2002, Pressure as a further parameter of composite curves in energy process integration, CHISA 2002 Proceedings, Set 4, PRES 2002, P 5.75.
- Václavek V., Novotná A., and Dedková J., 2003, Pressure as a further parameter of composite curves in energy process integration, Appl Therm Eng 23, 1785–1795.
- Varbanov P., Perry S., Klemeš J. and Smith R., 2005, Synthesis of industrial utility systems: cost-effective decarbonisation, Appl Thermal Engng 25 (7), 985–1001.
- Varbanov P.S., Doyle S. and Smith R., 2004, Modelling and Optimisation of Utility Systems, Trans IChemE – Chem Eng Res Des 82(A5), 561-578.
- Varbanov P.S., Klemeš J., 1999, Rules for paths construction for HENS debottlenecking, PRES'99 Proceedings, ed. F. Friedler and J Klemeš, Hungarian Chemical Society, Budapest, 685-690.
- Varbanov P.S., Klemeš J., 2000, Rules for paths construction for HENS debottlenecking, Applied Thermal Engineering 20(15-16), 1409-1420.
- Wang Y.P. and Smith, R., 1994, Wastewater minimisation, Chemical Engineering Science 49(7), 981-1006.
- Wising U., Berntsson T. and Stuart P., 2005, The potential for energy savings when reducing the water consumption in a kraft pulp mill, Appl Ther Eng. r25 1057–1066.
- Zhelev T. and Bhaw N., 1999, Combined water-oxygen pinch analysis for better wastewater treatment management. PRES'99 Proceedings, ed. F. Friedler and J. Klemeš, Hungarian Chemical Society, Budapest, 731-736.
- Zhelev T. and Ntlhakana L., 1999. Energy-environment closed loop through oxygen pinch, Computers & Chemical Engineering 23(Supplement), S79-S83.
- Zhelev T.K. and Bhaw N., 2000, Combined water–oxygen pinch analysis for better wastewater treatment management, Waste Management 20(8), 665-670.
- Zhelev T.K., 2003, On the integrated management of industrial resources incorporating finances. Sustainable systems theory: ecological and other aspects, PRES'03/ CSE;03, Hamilton, Canada, 550.
- Zhelev T.K., 2005a, On the integrated management of industrial resources incorporating finances. Sustainable systems theory: ecological and other aspects, Journal of Cleaner Production 13, 469 – 474.
- Zhelev T.K., 2005b, Water conservation through energy management, Journal of Cleaner Production 13, 1461–1470.
- Zhu X.X. and Vaideeswaran L., 1999, Recent research development of process integration in analysis and optimisation of energy system. PRES'99 Proceedings, ed. F. Friedler and J Klemeš, Hungarian Chemical Society, Budapest, 87-94.
- Zhu X.X., Zafir M. and Klemeš J., 1998, Heat Transfer Enhancement for Heat Exchange Network Retrofit. CHISA'98/1st Conference PRES'98, Prague, F4.4 [444]
- Zhu X.X., Zafir M. and Klemeš J., 2000, Heat Transfer Enhancement for Heat Exchanger Network Retrofit, Heat Transfer Engineering 21 (2), 7-18.