

VOL. 88, 2021



DOI: 10.3303/CET2188143

Guest Editors: Petar S. Varbanov, Yee Van Fan, Jiří J. Klemeš Copyright © 2021, AIDIC Servizi S.r.l. **ISBN** 978-88-95608-86-0; **ISSN** 2283-9216

Lean Sustainable Competitive Manufacturing Strategy Assessment: A Case Study in the Indonesian Car Manufacturing Company

Emelia Sari^{a,*}, Iveline A. Marie^a, Erika Erika^a, Abdoulmohammad G. Chofreh^b, Feybi A. Goni^c, Jiří Jaromír Klemeš^b, Masoomeh Zeinalnezhad^d

^aUniversitas Trisakti, Faculty of Industrial Technology, Department of Industrial Engineering, 11440, Kyai Tapa No 1, West Jakarta, Indonesia

^bSustainable Process Integration Laboratory – SPIL, NETME Centre, Faculty of Mechanical Engineering, Brno University of Technology - VUT Brno, Technická 2896/2, 616 69 Brno, Czech Republic

^oDepartment of Management, Faculty of Business and Management, Brno University of Technology - VUT Brno, Kolejní 2906/4, 61200 Brno, Czech Republic

^dDepartment of Industrial Engineering, West Tehran Branch, Islamic Azad University, Tehran, Iran emelia@trisakti.ac.id

The scarcity of resources combined with the COVID-19 pandemic outbreak has forced the manufacturing companies to be more prudent in using their production resources such as raw materials, energy, and water. A lean sustainable production system is an effective Competitive Manufacturing Strategy (CMS) that enables companies to sustain their production by identifying the potential waste and pollution. This study aimed to propose a novel framework by combining Sustainable Value Stream Mapping (SVSM) by Hartini and Sustainability Index (SI) assessment model by Garbie to assess the contribution of lean sustainable CMS in enhancing manufacturing performance. An SVSM and pairwise comparison is used to measure the SI. The SVSM is applied to identify the waste, while the pairwise comparison is used to determine each performance indicator's weight. A case study is conducted in an Indonesian car manufacturing company to validate how the lean sustainable CMS improves the SI. The results of this study should guide the practitioners in a standard procedure for assessing the effectiveness of lean sustainable CMS. For academicians, the work provides empirical evidence of the positive impact of lean sustainable CMS practices on the SI.

1. Introduction

The deficiency of production resources, especially fossil energy (Chofreh et al., 2020), combined with the COVID-19 outbreak (Zeinalnezhad et al., 2020) and the government regulation (Goni et al., 2021), have forced the manufacturing companies regarding the sustainability issues in their daily production system. This problem also applies to car manufacturers (Sari et al., 2015), which are one of the manufacturers that are struggling towards a sustainable supply chain (Chofreh et al., 2016). A Lean Production System (LPS) is one of the main Competitive Manufacturing Strategies (CMS) to become more sustainable (Garbie, 2016). Hartini et al. (2020) stated that Sustainable Value Stream Mapping (SVSM) is an effective tool of LPS for identifying improper manufacturing processes to avoid waste and pollution. Therefore, the company can define the room for optimal improvements in the utilisation of production resources sustaining profit, being environmentally benign, and safe for all stakeholders.

Choudhary et al. (2019) stated that LPS needs a tool named Value Stream Mapping (VSM) to evaluate its effectiveness in improving sustainable performance. Previous researchers have developed VSM. However, they are focused on partially sustainability factors rather than integrating all of them. It has been proved in the work of Edtmayr et al. (2016), which considered the economic and environmental factors in developing VSM to enhance green automotive manufacturer performance. They developed VSM concerning time, energy, waste, water, solvents, and CO₂ for evaluating the effectiveness of the three R basic strategies (reuse, recycle,

Paper Received: 1 June 2021; Revised: 6 September 2021; Accepted: 3 October 2021

Please cite this article as: Sari E., Marie I.A., Erika E., Chofreh A.G., Goni F.A., Klemeš J.J., Zeinalnezhad M., 2021, Lean Sustainable Competitive Manufacturing Strategy Assessment: A Case Study in the Indonesian Car Manufacturing Company, Chemical Engineering Transactions, 88, 859-864 DOI:10.3303/CET2188143 recovery) in preventing waste and pollution and enhancing resources efficiency. Muñoz-Villamizar et al. (2019) proposed VSM that integrates an environmental perspective named Overall Greenness Performance (OGP) for VSM. This study conducted a case study in Spain automotive manufacturer for measuring performance concerning time, energy use, solvent use, and air emission. The results revelated that the integration of lean and green enables enhancing the manufacturing performance. However, their OGP-VSM does not consider physical work and environment work (social factor). Currently, Gholami et al. (2021) proposed a VSM that combines the lean, green, and six sigma methodologies to measure the performance of the Malaysian substrate manufacturing system concerning time and using of production resources (energy, water, and chemical).

Faulkner and Badurdeen (2014) are among the first authors to propose a comprehensive SVSM that considers six indicators for measuring the implication of the production process. The SVSM validated in the US satellite television dishes manufacturer that focused evaluating the use of production resources (time, raw material, energy, water), environmental burden, and physical effect of the worker. Hartini et al. (2020) developed a single framework that applied SVSM, Delphi Method, and Analytical Hierarchy Process approach to evaluate sustainable manufacturing performance in the Indonesian wooden furniture industry. This framework consists of 11 indicators related to conventional lean and three pillars of sustainability. Table 1 presents the identified VSM indicators in the manufacturing industry. It shows that all authors have considered economic and environmental factors in their VSM and social factors as emerging factors in developing VSM.

This study aimed to answer research questions on developing a simple and comprehensive tool measuring the contribution of lean CMS enhancing sustainable performance. To answer the issue, this study proposes an SVSM based on Hartini's model that considers three factors of sustainability and a methodology to assess the Sustainability Index (SI) based on Garbi's formula. The main advantage of this formula is that it does not require a normalisation process converting different measurement units into dimensionless scores. Therefore, it enables simplifying the performance measurement process (Garbie, 2016). The remaining paper is structured into four sections. Section 2 shows the research approach for assessing the SI. Section 3 discusses the results of this study. Finally, section 4 concludes this study.

Authors	Cost					Environmental					Social				
	C1	C2	C3	C4	C5	E1	E2	E3	E4	E5	E6	S1	S2	S3	S4
Brown et al. (2014)															
Faulkner and						\checkmark			\checkmark				\checkmark		
Badurdeen (2014)															
Nallusamy et al. (2015)															
Edtmayr et al. (2016)								\checkmark	\checkmark	\checkmark	\checkmark				
Garza-Reyes et al. (2018)	\checkmark						\checkmark								
Hartini et al. (2018)			\checkmark			\checkmark		\checkmark		\checkmark			\checkmark		\checkmark
Choudhary et al. (2019)											\checkmark				
Gholami et al. (2019)													\checkmark		
Maqbool et al. (2019)															
Muñoz-Villamizar															
et al. (2019)															
Hartini et al. (2020)								\checkmark					\checkmark		\checkmark
Marie et al. (2020)				\checkmark		\checkmark							\checkmark		
Samant and Prakash															
(2020)															
Gholami et al. (2021)									\checkmark	\checkmark					
Viles et al. (2021)									\checkmark						
Selected indicators	\checkmark						\checkmark	\checkmark				\checkmark	\checkmark	\checkmark	\checkmark

Table 1: The SVSM indicators identified in the manufacturing industry

Cost: ^{C1} Time; ^{C2} Cost; ^{C3} Inventory; ^{C4} Quality compliance and product defect; ^{C5} Changeover time **Environmental:** ^{E1} Material consumption; ^{E2} Energy consumption; ^{E3} Waste recycling; ^{E4} Water consumption; ^{E5} Hazard material; ^{E6} Air pollution

Social: ^{S1} Satisfaction level; ^{S2} Work environment: noise level and lighting level; ^{S3} Physical work: activity with risk and lost workday; ^{S4} Employee training

860

2. Research approaches

This stage consists of two main sections concerning developing the measurement indicator and measuring steps of SI.

2.1 Defining the sustainable value stream mapping and sustainability index indicators

This section comprises three steps. First, the list of initial SVSM and SI indicators are elaborated based on the previous studies. This study categorised 15 initial indicators into three pillars of sustainability (see Table 1). Second, the initial indicators were validated by the experts through the interview process. The case study was conducted at an Indonesian car manufacturing company that produces Truck Colt Diesel (TCD). In this study, indicators related to planned maintenance program achievement are embedded (Sari et al., 2014). Third, this study selected 13 indicators based on the objectives, characteristics, and limitations of the case study company.

2.2 Creating current sustainable value stream mapping and measuring sustainability index

This section composes of two main processes. First, creating the current SVSM based on Hartini's study (Hartini et al., 2020). This SVSM considers the three factors of sustainability and uses a traffic light system. This system is used for classifying the actual achievement of each indicator and actions needed for improvement. The green colour explains that the actual achievement meets the target and can be further improved by a routine program. The yellow colour signs that actual achievement falls slightly below the target value, and corrective action is needed. The red colour explains that the actual achievement falls slightly below the target value and corrective action needs to be taken immediately. The management level determines the target value of each indicator. Second, measuring the SI using Garbie's formula as following (Garbie, 2016).

- Rate the target value (S) of each indicator by the top management level.
- Rate the actual achievement value (E) of each indicator by the top management level.
 Rate the actual achievement value (E) of each indicator by top management level.
- Determine the value of change for each indicator (S E).
- Calculating the SI for economic (SIEc), social (SISc), and environmental (SIEn) factors Eq(1) and Eq(2).

$$SI = \left(\frac{S_{i1}}{E_{i1}}\right)^{Yi1} x \left(\frac{S_{i2}}{E_{i2}}\right)^{Yi2} \dots x \left(\frac{S_{nij}}{E_{nij}}\right)^{Ynij}$$
(1)

 $Y_{ij} = \log |S_{ij} - E_{ij}|$

- Compute the relative importance weight (W) of factors by expert's judgment using Saaty's nine-point scale.
- Calculate the overall score of SI using Eq(3).

 $Overall SI = (W_{Ec} \times SI_{Ec}) + (W_{Sc} \times SI_{Sc}) + (W_{En} \times SI_{En})$

3. Results and discussion

There are two main results of this study, i.e., current SVSM and overall SI for the case study company.

3.1 The current sustainable value stream mapping

This study developed an SVSM that consists of material and manufacturing process flow to identify Non-Value-Added Activity (NVA) and inefficiency of resources utilisation, as presented in Figure 1. The SVSM shows three main information related to time, Kaizen Burst, and dashboard actual achievement of each indicator.

The Kaizen burst reveals some waste and problems concerning economic (blue), social (yellow), and environmental (green) factors. In terms of the economy, the current SVSM identifies three waste (motion, defect, delay) and one problem, i.e., process time too long. There are three problems concerning social, i.e., PSW often failed, work position of operators is not ergonomic, and transportation without material handling. Regarding environmental, there are two problems, i.e., energy consumption too high and low lighting level.

The dashboard of actual achievement for each indicator is presented in three traffic lights colours. There are 4 out of 5 indicators below the target (yellow) regarded economic factor. Time is the main indicator of traditional lean manufacturing (Hartini et al., 2020). SVSM shows that the achievement of this indicator is 85 % out of 100 %. The actual achievement of the defect indicator is 13 % out of 4 %. The quality of raw material from suppliers achieved 80 % out of 100 %. Concerning the maintenance program, the company has executed 75 % of the planned maintenance program. It needs to be enhanced since a sustainable maintenance program enables optimising the use of production resources and impeding waste and pollution, specifically in the automotive industry (Sari et al., 2021). The compliance with quality standards and environmental regulations, the company

(2)

(3)

has been certified with ISO 9001:2008, ISO 9001:2015, ISO 14000, and IATF 16949:2016. The achievement of this indicator is 100 % (green). In terms of social factors, there are 3 out of 6 indicators below the target (activity with risk, noise level, and satisfaction level), and 3 out of 6 indicators have achieved the target named lost workday, lighting level, and employee training. All indicators fall well below the target value (red) concerning environmental factors, so they need to be solved immediately. First, energy consumption is needed for the production process. Edtmayr et al. (2016) stated that non-renewable energy consumption during the production process directly relates to GHG emissions. SVSM shows the energy consumption of the TCD falls well below the target value, i.e., 990 MJ. Second, wastewater that has been recycled is 60 %. Viles et al. (2021) stated that water is becoming a critical production resource, and the company needs to develop a strategy that enables water recycled 100 % to achieve a zero-waste strategy.





3.2 The Sustainability Index

This section presents the SI achievement of the case study company, i.e., 79 % for economic, 312 % for social, and 188 % for environmental factors, as shown in Table 2. To calculate the overall SI, the management level of the case study company determined the relative importance of each factor, i.e., 0.74, 0.17, and 0.09 for economic, social, and environmental. Finally, the overall SI is 128 % which needs 1.28 times more effort concerning time and cost than exiting conditions to be sustainable.

Table 2: Sustainability index

Factor/ Indicator		% Measure	Actual	Target	Value of change	SI (Factor)	Eigen- vector	Overall SI
	Time	%	85	100	15			
Economic	Compliance with quality standards and environmental regulation	%	100	100	0			128 %
	Defect	%	13	4	9	79 %	0.74	
	Quality of raw material	%	80	100	20			
	Planned Maintenance program achievement	% (month)	75	100	25			
Social	Activity with risk	%	72	100	28			
	Lost workday	%	0.25	0	0.25			
	Noise level	dB	74.53	85	10.47			
	Lighting level	Lux	256 - 452	200 - 500	0	312 %	0.17	
	Employee training	Topics (month)	3	3	0	512 /0		
	Satisfaction level	%	70	100	30			
Environ- mental	Energy consumption	MJ	990	900	90	199.0/	0.00	
	Wastewater recycling	%	60	100	40	100 70	0.09	

4. Conclusions

This study proposed a simple and comprehensive SVSM framework for assessing the contribution of lean, competitive manufacturing strategy enhancing SI. The SVSM enables the identification of waste and the actual achievement of each indicator, then the actions needed for improving the overall SI can be formulated. The overall SI value for the case study company is 128 %. Moreover, two indicators concerning environmental, i.e. energy consumption and waste-water recycling, fall well below the target value (red zone), corrective action needs to be taken immediately to improve the achievement of these indicators.

The results of this study would advance the SVSM framework by providing a list of important indicators that need to be considered in assessing the contribution of LPS to become a more sustainable company. The authors will continue the study identifying the waste and proposes an improvement program. Next, the methodology for creating SVSM and calculating SI after improvement will be developed.

This study has limitations regarding the weight of each indicator since the weights are determined by the case study company experts. The standard weight of each indicator is thus required for a specific industry, and the future study can conduct a large survey to determine these weights.

Finally, this SVSM is developed based on the case of an Indonesian car manufacturing company. It can be used for other companies by reshaping the SVSM concerning their internal condition and external pressure.

Acknowledgements

This research is supported by Internal Research Grant under the Universitas Trisakti (Grant No. 51.02.02.02). The authors highly acknowledge financial support from the project "Sustainable Process Integration Laboratory – SPIL funded by EU - CZ Operational Programme Research and Development, Education, Priority1: Strengthening capacity for quality research" (Grant No. CZ.02.1.01/0.0/0.0/15_003/000045).

References

Brown A., Amundson J., Badurdeen F., 2014, Sustainable value stream mapping (Sus-VSM) in different manufacturing system configurations: application case studies, Journal of Cleaner Production, 85, 164-179.

- Chofreh A.G., Goni F.A., Klemeš J.J., 2016, A master plan for the implementation of sustainable enterprise resource planning systems (Part II): development of a roadmap, Chemical Engineering Transactions, 52, 1099-1104.
- Chofreh A.G., Goni F.A., Klemeš J.J., Seyed Moosavi S.M., Davoudi M., Zeinalnezhad M., 2020, COVID-19 shock: development of strategic management framework for global energy, Renewable and Sustainable Energy Reviews, 110643.
- Choudhary S., Nayak R., Dora M., Mishra N., Ghadge A., 2019, An integrated lean and green approach for improving sustainability performance: a case study of a packaging manufacturing SME in the U.K., Production Planning & Control, 30(5-6), 353-368.
- Edtmayr T., Sunk A., Sihn W., 2016, An approach to integrate parameters and indicators of sustainability management into value steam mapping, Procedia CIRP, 41, 289-294.
- Faulkner W., Badurdeen F., 2014, Sustainable value stream mapping (Sus-VSM): methodology to visualize and assess manufacturing sustainability performance, Journal of Cleaner Production, 85, 8-18.
- Garbie I., 2016, Sustainability in Manufacturing Enterprises: Concepts, Analyses and Assessments for Industry 4.0, Springer Nature, Switzerland.
- Garza-Reyes J.A., -Romero J.T., Govindan K., Cherrafi A., Ramanathan U., 2018, A PDCA-based approach to environmental value stream mapping (E-VSM), Journal of Cleaner Production, 180, 335-348.
- Gholami H., Jamil N., Zakuan N., Mat Saman M.Z., Sharif S., Awang S.R., Sulaiman Z., 2019, Social value stream mapping (Socio-VSM): methodology to societal sustainability visualization and assessment in the manufacturing system, IEEE Access, 7, 131638-131648.
- Gholami H., Jamil N., Mat Saman M.Z., Streimikiene D., Sharif S., Zakuan N., 2021, The application of green lean six sigma, Business Strategy and the Environment, 30(4), 1913-1931.
- Goni F.A., Chofreh A.G., Orakani Z.E., Klemeš J.J., Davoudi M., Mardani A., 2021, Sustainable business model: a review and framework development. Clean Technologies and Environmental Policy, 23(3), 889-897.
- Hartini S., Ciptomulyono U., Anityasari M., Sriyanto, Pudjotomo, D., 2018, Sustainable-value stream mapping to evaluate sustainability performance: case study in an Indonesian furniture company, MATEC Web of Conferences, 154, 01055.
- Hartini S., Ciptomulyono U., Anityasari M., Sriyanto, 2020, Manufacturing sustainability assessment using a lean manufacturing tool, International Journal of Lean Six Sigma, 11(5), 957-985.
- Marie I.A., Sari E., Lika C.A., 2020, Enhancing sustainable maintenance performance using lean competitive manufacturing strategy: a case study in steel company, Solid State Technology, 63(6), 902-917.
- Maqbool Y., Rafique M.Z., Hussain A., Ali H., Javed S., Amjad M.S., Khan M.A., Mumtaz S., Haider S.M., Atif M., 2019, An implementation framework to attain 6R-based sustainable lean implementation—a case study, IEEE Access, 7, 117561-117579.
- Muñoz-Villamizar A., Santos J., Garcia-Sabater J.J., Lleo A., Grau P., 2019, Green value stream mapping approach to improving productivity and environmental performance, International Journal of Productivity and Performance Management, 68(3), 608-625.
- Nallusamy Dr. S., Dinagaraj G.B., Balakannan K., Satheesh S., 2015, Sustainable green lean manufacturing practices in small scale industries – a case study, International Journal of Applied Engineering Research, 10(62), 143-146.
- Samant S., Prakash R., 2020, Achieving lean and improving sustainability through value stream mapping for complex manufacturing, IOP Conference Series: Materials Science and Engineering, 748, 012022.
- Sari E., Shaharoun A.B., Ma'aram A.B., 2014, Preliminary framework of sustainable maintenance performance measurement systems for automotive companies, Advanced Materials Research, 845, 590-595.
- Sari E., Shaharoun A.M., Ma'aram A., Yazid, A.M., 2015, Sustainable maintenance performance measures: a pilot survey in Malaysian automotive companies, Procedia CIRP, 26, 443-448.
- Sari E., Ma'aram A., Shaharoun A.M., Chofreh A.G., Goni F.A., Klemeš J.J., Marie I.A., Saraswati D., 2021, Measuring sustainable cleaner maintenance hierarchical contributions of the car manufacturing industry, Journal of Cleaner Production, 312, 127717.
- Viles E., Santos J., Muñoz-Villamizar A., Grau P., Fernández-Arévalo T., 2021, Lean–green improvement opportunities for sustainable manufacturing using water telemetry in agri-food industry, Sustainability, 13(4), 2240.
- Zeinalnezhad M., Chofreh A.G., Goni F.A., Klemeš J.J., Sari, E, 2020, Simulation and improvement of patients' workflow in heart clinics during COVID-19 pandemic using timed coloured Petri nets, International Journal of Environmental Research and Public Health, 17(22), 8577.