

VOL. 57, 2017



Guest Editors: Sauro Pierucci, Jiří Jaromír Klemeš, Laura Piazza, Serafim Bakalis Copyright © 2017, AIDIC Servizi S.r.I. **ISBN** 978-88-95608- 48-8; **ISSN** 2283-9216

# Modeling Vapor Liquid Equilibrium of Binary and Ternary Systems of CO<sub>2</sub> + Hydrocarbons at High-Pressure Conditions

Dennys C. Silva<sup>a</sup>, Reginaldo Guirardello<sup>b</sup>, Antonio C. D. Freitas<sup>\*b</sup>

<sup>a</sup>Chemical Engineering Coordination, Exact Sciences and Technology Center, Federal University of Maranhão (UFMA), Av. dos Portugueses, 1966, Bacanga, 65080-805, São Luís-MA, Brazil.

<sup>b</sup>School of Chemical Engineering, University of Campinas (UNICAMP), Av. Albert Einstein 500, 13083-852, Campinas-SP, Brazil

acd.freitas@ufma.br

In this work, binary and ternary systems composed by hydrocarbons and  $CO_2$  in liquid-vapor equilibrium conditions (LV) were thermodynamically modeled using Peng-Robinson (PR) and Patel-Teja (PT) equations of state (EoS) in combination with van der Waals mixing rule with two adjustable parameters (vdW-2,  $k_{ij}$  and  $l_{ij}$ ). The model was formulated as a minimization of the Mean Absolute Deviation (%AAD) between the predicted and experimental values for liquid and vapor phases using the simplex algorithm, through the software Phase-Equilibrium 2000 (*PE-2000*). Low deviations, %AAD = 2.33% for PR EoS and %AAD = 3.06% for PT EoS were observed for binary systems in the evaluation of 160 experimental points (EP). Ternary systems were modeled with low deviations too, %AAD = 1.12% for EoS PR and %AAD = 1.18% for EoS PT were observed in the evaluation of 69 EP. Both tested EoS proved to be useful to represent LV equilibrium in this kind of system.

## 1. Introduction

The use of  $CO_2$  in the chemical industry has increased in recent years due to its properties as a solvent, especially at supercritical conditions. Accurate data for liquid-vapor equilibrium for systems composed by carbon dioxide, hydrocarbons, ethanol and water are important for designing separation processes and synthesis reactions from syngas, such as Fischer-Tropsch synthesis (Freitas and Guirardello, 2015) and are useful for supercritical fluids technology, applications can be found in chemical, petrochemical and food industry (Gallegos et al., 2006).

The prediction and description of thermodynamic properties and phase equilibria of multicomponent mixtures remains a major challenge in the scientific community at the same time becomes a necessity in the industrial environment. Despite the wide range of applications, the use equations of EoS to model systems composed by  $CO_2$  and hydrocarbons are very rare in the literature. Studies that determine the parameters to represent liquid vapor equilibrium for this kind of systems using cubic EoS are scarce, however, these kind of study are essential for some applications, including the use of these equations in modeling and simulation of chemical processes with greater confidence.

In this context, the main objective of this paper was the use of Peng-Robinson (PR) and Patel-Teja (PT) equations of state in combination with van der Waals mixing rule with 2 adjustable parameters (vdW-2,  $k_{ij}$  and  $l_{ij}$ ) to determine binary interaction parameters for systems composed by CO<sub>2</sub> and hydrocarbons in binary and ternary systems. For this, the software Phase Equilibrium 2000 (*PE-2000*) was used in combination with simplex Nelder-Mead algorithm to minimize an objective function based on average deviations observed between molar fractions of liquid and vapor phases.

# 2. Methodology

# 2.1. Peng-Robinson EoS (PR)

The expression for Peng-Robinson (PR) EoS (Peng and Robinson, 1976) is represented by:

$$P = \frac{RT}{V - b} - \frac{\alpha(T)}{V(V + b) + b(V - b)}$$
(1)

Here, *P* is the pressure, *V* is the molar volume, *T* is the temperature,  $\alpha(T)$  is the temperature-dependent attractive parameter, *b* is the co-volume and *R* is the ideal gas constant. The co-volume parameter is temperature independent and is calculated using the critical properties of the pure component as follows:

$$b = 0,0778 \frac{\kappa_{I_C}}{P_C}$$
(2)

The attractive parameter,  $\alpha(T)$ , is calculated by:

$$\alpha = 0.45724 \frac{(RT_C)^2}{P_C} \left[ 1 + (0.37464 + 1.5422\omega - 0.26992\omega^2) (1 - T_r^{0.5}) \right]^2$$
(3)

#### 2.2. Patel-Teja EoS (PT)

The expression for Patel and Teja (PT) EoS (Patel and Teja, 1982) is represented by:

$$P = \frac{RI}{V - b} - \frac{a}{V(V + b) + c(V - b)}$$
(4)

The variables are the same explained above for PR EoS. The parameters a, b and c are:

$$a = 0,66121 - 0,761057Z_{C} \frac{R^{21}\tilde{c}}{P_{C}^{2}} \left[ 1 + (0,46283 + 3,58230\omega Z_{C} + 8,19417(\omega Z_{C})^{2}) (1 - \sqrt{T_{r}}) \right]^{2}$$
(5)

$$b = 0,02207 - 0,20868Z_C \frac{RT_C}{P_C}$$
(6)

$$c = 0,57765 - 1,87080Z_C \frac{RT_C}{P_C}$$
(7)

## 2.3 van der Waals mixing rule

PR and PT EoS were applied in combination with the van der Waals mixing rule with two adjustable parameters ( $k_{ij}$  and  $l_{ij}$ ) (vdW-2). The  $a_{mix}$  and  $b_{mix}$  parameters are presented in equations (8) and (9) respectively.

$$a_{mix} = \sum_{i} \sum_{j} x_{i} x_{j} (\alpha_{i} \alpha_{j})^{0.5} (1 - k_{ij})$$
(8)

$$b_{mix} = \sum_{i} \sum_{i} \sum_{j} x_i x_j \frac{1}{2} (b_i + b_j) (1 - l_{ij})$$
(9)

with  $k_{ij} = k_{ji}$  and  $I_{ij} = I_{ji}$ .

## 2.4. PE 2000 software

The software Phase Equilibrium 2000 (*PE-2000*), developed by Brunner and coworkers (Pfohl and Petkov, 2000), uses the Simplex modified algorithm to regression of interaction parameters, minimizing the objective function of the absolute average deviation (%AAD) to molar fractions of liquid and vapor phase, as shown in:

$$\%AAD = \frac{100}{NP} \left( \sum_{i=1}^{N} |x_i^{exp} - x_i^{pred}| + \sum_{i=1}^{N} |y_i^{exp} - y_i^{pred}| \right)$$
(10)

Here,  $x_i^{exp}$  is the experimental liquid mole fraction data;  $x_i^{pred}$  is the predicted value;  $y_i^{exp}$  is the experimental vapor mole fraction data;  $y_i^{pred}$  is the predicted value and NP is the number of experimental data points used in the regression procedure. Several initial estimates were used to avoid the local minima in the regression in order to guarantee that the obtained values ate the global minimum to evaluated parameters ( $k_{ij}$  and  $l_{ij}$ ).

The software PE 2000 has already been used in other studies with excellent results to correlate and predict phase behavior for different systems under conditions of liquid-liquid-vapor and liquid-vapor equilibrium (Freitas et al., 2013).

#### 2.5. CO<sub>2</sub>+hydrocarbons systems

The 7 binary and 2 ternary systems studied in this work and the source of experimental data are presented in Table 1. The characteristics of the studied systems, including pressure, temperature and composition range of the experimental data are presented in this table as well.

The experimental data were taken from the literature as presented in Table 1 for all studied binary and ternary systems. The critical properties of all compounds studied in this work are obtained in literature as well (Poling et al., 2001).

	System			References		
			T (K)	P (bar)	X <sub>CO2</sub>	-
Binary	CO <sub>2</sub> + CH <sub>4</sub>	24	240.35-261.25	18.3-82.4	0.0193-0.4206	Nasir et al. (2015)
Systems	$CO_2 + C_3H_8$	20	252.95-273.15	3.3-33.9	0.013-0.953	Nagahama et al. (1969)
	CO <sub>2</sub> + C <sub>4</sub> H <sub>10</sub>	13	273.15	2.4-31.5	0.03-0.911	Nagahama et al. (1969)
	CO <sub>2</sub> + C <sub>8</sub> H <sub>18</sub>	28	322.39-372.53	20.13-137.72	0.1422-0.8892	Gallegos et al. (2006)
	$CO_2 + C_{10}H_{22}$	29	319.11-372.94	32.41-160.6	0.2146-0.9731	Gallegos et al. (2006)
	$CO_2 + C_5H_{10}$	27	323.15-344.65	6.3-96.2	0.0442-0.855	Sima et al. (2016)
	$CO_2 + C_6H_{12}$	19	323.15-353.15	10-110.1	0.108-0.7754	Sima et al. (2016)
Ternary	$CO_2 + CH_4 + C_3H_8$	54	230-270	8-80	0.0021-0.7377	Webster and Kidnay
Systems						(2001)
	$CO_2 + CH_4 + C_2H_6$	15	250	21-30	0.0812-0.8992	Davalos et al. (1976)

Table 1: Identification of binary and ternary systems studied in this work.

# 3. Results and discussion

## 3.1 Binary systems

The determined adjustable parameters,  $k_{ij}$  and  $l_{ij}$  and the %AAD as function of systems temperature are shown in Table 2 for all 7 binary systems analyzed here (17 isotherms with a total of 160 EP). Figures 1-2 shows the comparison between calculated and experimental data for the mole fraction of liquid and vapor phase for all seven systems at all temperatures and deviations in calculated pressure for both EoS analyzed. Figure 1 shows the results for PR-vdW-2 EoS determinations and Figure 2 shows the results for PT-vdW-2 EoS determinations.

Analyzing Figures 1, 2, and Table 2, it can be verified that a good correlation between experimental and calculated data was obtained for most part of systems analyzed, with low computational time (less than 5 minutes) for all cases. Larger deviations were observed for PT EoS.

The phase behavior of all analyzed systems showed an increase in the solubility of  $CO_2$  in hydrocarbons with increasing in system pressure. This behavior was observed for all compounds evaluated in this work, and the increase in temperature resulted in a decrease in  $CO_2$  composition in the vapor phase, this trend was observed for all studied systems too. In general was observed that liquid phase predictions from EoS are worse than that observed for vapor phase. The most dissonant points for the upper curve, in both cases, refer to the system  $C_5H_{10} + CO_2$ , which may indicate some deviations in experimental data obtained by Sima et al. (2016). In addition, there is a higher concentration of the experimental data in the region of higher to vapor phase compositions. This behavior can be explained by the lower solubility of  $CO_2$  in hydrocarbons with more than 4 carbons in chain. Similar trends were described in Freitas et al. (2013) for systems composed by ionic liquids and  $CO_2$  at high pressure conditions.

*Table 2:* Binary interaction parameters and deviation at different temperatures for PR and PR EoS combined with vdW-2 mixing rule.

	-		PR		PT				
System	T (K)	k <sub>ij</sub>	l <sub>ij</sub>	%AAD	T (K)	k <sub>ij</sub>	l <sub>ij</sub>	%AAD	
$CO_2 + CH_4$	240.35	0.0567	-0.0615	3.87	240.35	0.0595	-0.0575	4.01	
	250.00	0.0691	-0.0514	2.70	250.00	0.0723	-0.0465	2.89	
	261.25	0.0555	-0.0571	1.70	261.25	0.0587	-0.0536	1.90	
$CO_2 + C_3H_8$	252.95	0.0786	-0.0384	2.90	252.95	-0.0150	-0.2256	3.90	
	273.15	-0.0226	-0.2066	3.81	273.15	0.0769	-0.0502	2.94	
$CO_2 + C_4H_{10}$	273.15	0.0795	-0.0365	1.28	273.15	0.0825	-0.0393	3.40	
$CO_2 + C_8H_{18}$	322.39	0.0931	-0.0099	1.16	322.39	0.1006	-5.36E-5	1.72	
	348.25	0.1117	-0.0033	1.71	348.25	0.0825	-0.0096	0.08	
	372.53	0.1149	-0.0082	2.31	372.53	0.1036	-0.0048	2.26	
$CO_2 + C_{10}H_{22}$	319.11	0.0885	-0.0268	1.06	319.11	0.0489	-0.0356	4.15	
	344.74	0.0883	0.0122	3.42	344.74	0.0687	0.0248	3.64	
	372.94	0.0985	0.0001	1.64	372.94	0.0790	0.0115	1.72	
$CO_2 + C_5H_{10}$	323.15	0.1159	0.1131	6.17	323.15	0.1131	0.1209	6.11	
	333.15	0.1234	0.1630	8.19	333.15	0.1179	0.1752	8.16	
	344.65	0.1638	0.1999	8.16	344.65	0.1669	0.2281	8.16	
$CO_2 + C_6H_{12}$	323.15	0.1006	-0.0287	1.54	323.15	0.1031	-0.0328	1.63	
	353.15	0.1101	0.0301	2.36	353.15	0.1099	0.0296	3.06	
Mean deviation	-	-	-	2.36	-	-	-	3.06	



Figure 1. Comparison of calculated and experimental data for the mole fraction of liquid phase (a) and vapor phase (b) using PR-vdW-2 (binary systems).



Figure 2. Comparison of calculated and experimental data for the mole fraction of liquid phase (a) and vapor phase (b) using PT-vdW-2 (binary systems).

Overall, and as expected for this type of thermodynamic model, the ability of the PR and PT EoS when combined with the vdW-2-mixing rule, for representation of vapor phase behavior was greater than that observed for the liquid phase. The results obtained by Shariati et al. (1998) for multicomponent systems formed by hydrocarbons and carbon dioxide, using PR-EoS showed similar behavior to that observed in this work.

# 3.2 Ternary systems

The adjustable parameters,  $k_{ij}$  and  $l_{ij}$  and the %AAD as function of pressure and temperature are presented in Table 3 (results for  $k_{ij}$ ) and Table 4 (results for  $l_{ij}$ ) for the 2 ternary systems analyzed in this work, totalizing a total 69 experimental data points.

			PR				PT			
System	<i>т (</i> к)	P (bar)	<b>k</b> ij	<b>k</b> ij	<b>k</b> ij	AAD	<b>k</b> ij	<b>k</b> ij	<b>k</b> ij	AAD
	, (14)	. (	i = 1; j = 2	i = 1; j = 3	i = 2; j = 3	(%)	i = 1; j = 2	i = 1; j = 3	i = 2; j = 3	(%)
$CO_2 + CH_4 + C_3H$	8 230	8	1.273	0.119	0.498	5.32	0.285	0.122	-0.148	5.04
	230	40	0.098	0.069	0.011	0.79	0.103	0.106	0.006	0.42
	230	70	0.187	0.095	-0.001	0.48	0.195	0.097	-0.005	0.21
	270	28	-0.200	0.216	0.236	6.81	-0.164	-0.374	0.141	6.84
	270	55	0.113	0.191	0.025	0.26	0.107	0.189	0.024	0.26
	270	80	0.143	0.093	0.007	0.21	0.150	0.094	-0.0006	0.10
$CO_2 + CH_4 + C_2H$	6 250	21	-0.017	0.004	-2.332	3.73	0.004	0.524	-2.761	3.22
	250	25	0.129	0.041	-0.038	1.12	0.151	-0.107	-0.053	1.18
	250	30	0.080	0.284	-0.161	1.56	0.062	0.451	-0.115	1.54
Mean deviation	-	-	-	-	-	1.12	-	-	-	1.18

Table 3: Interaction parameters  $k_{ij}$  ( $k_{ij} = k_{ji}$ ) for the two ternary systems studied at different temperatures (K) and pressures (bar) for PR and PT EoS ( $k_{ij, i=j} = 0,000$ ).

Figures 3 and 4 shows the comparison between calculated and experimental data for the mole fraction of liquid and vapor phase for both systems at all conditions analyzed. Figure 3 presents the results for PR-vdW-2 EoS determinations and Figure 4 presents the results for PT-vdW-2 EoS determinations.

The same behavior observed for binary systems was observed here for the ternary systems too. The largest deviations were observed in the description of liquid phase, this trend is common for this type of model when used to perform the calculations carried out by this work using phi-phi ( $\phi - \phi$ ) formulation. The most dissonant points for the upper curve, in both cases, refer to lower pressure (8 and 28 bar to system 1 and 21 bar to the system 2).

Table 4: Interaction parameters  $I_{ij}$  ( $I_{ij} = I_{ji}$ ) for the two ternary systems studied at different temperatures (K) and pressures (bar) for PR and PT EoS ( $I_{ij, i=j} = 0,000$ ).

			PR				PT			
System	<i>Т</i> (К)	P (bar)	lij	l <sub>ij,</sub>	lij		lij	lij	lij	
Oystem			i = 1; j = 2	i = 1; j = 3	i = 2; j = 3	%AAD	i = 1; j = 2	i = 1; j = 3	i = 2; j = 3	%AAD
	230	8	1.092	-0.036	0.353	5.32	0.215	-0.040	-0.127	5.04
	230	40	-0.039	-0.055	0.008	0.79	-0.052	-0.002	0.009	0.42
	230	70	0.089	-0.028	-0.029	0.48	0.113	-0.028	-0.032	0.21
	270	28	-0.392	-0.094	0.186	6.81	-0.370	-0.688	0.126	6.84
	270	55	-0.020	0.078	0.022	0.26	-0.042	0.082	0.033	0.26
	270	80	0.019	-0.024	-0.007	0.21	0.024	-0.026	-0.012	0.10
	250	21	-0.187	-0.280	-2.551	3.73	-0.173	0.247	-3.192	3.22
	250	25	0.012	-0.072	-0.041	1.12	0.045	-0.228	-0.050	1.18
	250	30	-0.050	0.133	-0.187	1.56	-0.095	0.335	-0.133	1.54
Mean deviation	-	-	-	-	-	1.12	-	-	-	1.18



Figure 3. Comparison of calculated and experimental data for the mole fraction of liquid phase (a) and vapor phase (b) using PR-vdW-2 (ternary systems).



Figure 4. Comparison of calculated and experimental data for the mole fraction of liquid phase (a) and vapor phase (b) using PT-vdW-2 (ternary systems).

It is important to emphasize that the results obtained in this work are easily reproducible, since it were obtained by the use of a free software. Low deviations were observed, PR and PT EoS showed similar ability to represent this kind of experimental data in the ranges of pressure, temperature and composition tested in this work. Both EoS can be applied to describe the LV phase behavior of the systems studied with good results in further modelling and simulation of chemical processes.

## 4. Conclusions

In this study, binary interactions parameter for PR and PT EoS combined with vdW-2 mixing rule ( $k_{ij}$  and  $l_{ij}$ ), have been optimized for 7 binary mixtures and 2 ternary mixtures composed by hydrocarbons and carbon dioxide by a minimization of %AAD function using the Nelder-Mead Simplex-algorithm implemented in free software PE2000. Experimental data were obtained from the literature, a total of 160 data points, distributed in 17 isotherms, for the binary system and 69 experimental points for the ternary systems were studied.

Good results and low computational times (less than 5 minutes) were observed for all systems examined. For binary systems, regions of higher deviations were associated with conditions of low temperatures and high pressures, especially in the liquid phase, %AAD to 2.33% for PR EoS and 3.06% for PT EoS was determined for the evaluated systems. PR EoS presented lower deviations for these systems.

In ternary systems the larger deviations regions remains in liquid phase %AAD of 1.12% for PR EoS and 1.18% for PT EoS were detected in low pressure regions. One of the reasons that could have led to this difference would be the small amount of experimental data obtained in the literature for the representation of these systems and the condition of low temperature in which these data was measured. In this way, both EoS can be applied to describe the phase LV behavior of the systems studied with good results in further modelling and simulation of chemical processes.

## References

- Davalos J., Anderson W. R., Phelps R. E., Kidnay A. J., 1976. Liquid-Vapor Equilibria at 250.00 K for Systems containing Methane, Ethane, and Carbon Dioxide. Journal of Chemical and Engineering Data. 21 (1), 81-84.
- Freitas A. C. D., Cunico L. P., Aznar M., Guirardello, R., 2013. Modeling vapor liquid equilibrium of ionic liquids + gas binary systems at high pressure with cubic equations of state. Brazilian Journal of Chemical Engineering. 30 (1), 63-73.
- Freitas A. C. D., Guirardello R., 2015. Thermodynamic Characterization of Hydrocarbon Synthesis from Syngas using Fischer-Tropsch Type Reaction. Chemical Engineering Transactions, 43,1831-1836.
- Gallegos R. J., Galicia-Luna L. A., Elizalde-Solis, O., 2006. Experimental Vapor Liquid Equilibria for the Carbon Dioxide + Octane and Carbon Dioxide + Decane Systems. Journal of Chemical and Engineering Data, 51, 1624-1628
- Nagahama K., Konishi H., Hoshino D., Hirata, M., 1969. Binary vapor-liquid equilibria of carbon dioxide-light hydrocarbons at low temperature. Bulletin of the Japan Petroleum Institute. 11, 10-15.
- Nasir Q., Sabil K. M., Lau K. K., 2015. Measurement of isothermal (vapor + liquid) equilibria, (VLE) for binary (CH<sub>4</sub> + CO<sub>2</sub>) from T = (240.35 to 293.15) K and co2 rich synthetic natural gas systems from T = (248.15 to 279.15) K. Journal of Natural Gas Science and Engineering. 27,158-167.
- Patel N. C., Teja A. S., 1982. A new cubic equation of state for fluids and fluid mixtures. Chemical Engineering Science, 37 (3), 463-473.
- Peng D. Y., Robinson, D. B., 1976. A new two-constant equation of state. Industrial & Engineering Chemistry Research, 15, 59-64.
- Pfohl O., Petkov S., Brunner G., 2000. PE2000: a powerful tool to correlate phase equilibrium. Herbert Utzverlag, München.
- Poling B. E., Prausnitz J. M., O'Connell J. P. 2001. The Properties of Gases and Liquids, fifth edition. McGraw-Hill, New York, EUA.
- Shariati A., Peters C. J., Moshfeghian M., 1998. Buble point of some petroleum fractions in the presence of methane or carbon dioxide. Journal of Chemical Engineering Data. 43 (5), 789-790.
- Sima S., Milanesio J. M., Ramello J. I., Cismondi M., Secuianu C., Feroiu V., Geana D., 2016. The effect of the naphthenic ring on the VLE of (carbon dioxide + alkane) mixtures. Journal Chemical Thermodynamics, 93, 374-385.
- Webster L. A., Kidnay A. J., 2001. Vapor-Liquid Equilibria for the Methane-Propane-Carbon Dioxide System at 230 K and 270 K. Journal Chemical Engineering Data. 46, 759-764.